



For more Information  
please call

1-800-Belden1



### Description:

22 AWG Bare copper conductors, PP insulation, PVC jacket with ripcord. Sequential footage marking every two feet.

### Usage (Overall)

**Suitable Applications:** Security Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls, and Single Line Telephone.

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
4	22	7x30	BC - Bare Copper

**Total Number of Conductors:** 4

#### Insulation

**Insulation Material:**

Insulation Material	Wall Thickness (mm)
PP - Polypropylene	0.203

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.381

**Outer Jacket Ripcord:** Yes

#### Overall Cable

**Overall Cabling Lay Length & Direction:**

Length (mm)	Twists (twist/m)
101.5996	9.843

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	Red
3	White
4	Green

**Overall Nominal Diameter:** 3.581 mm

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +75°C

**UL Temperature Rating:** 75°C

**Bulk Cable Weight:** 19.347 Kg/Km

## 5502UE Multi-Conductor - Commercial Applications

Max. Recommended Pulling Tension: 161.914 N

Min. Bend Radius/Minor Axis: 34.925 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

NEC Articles: 800

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

#### Flame Test

UL Flame Test: UL1666 Vertical Shaft

C(UL) Flame Test: FT4

#### Plenum/Non-Plenum

Plenum Number: 6502UE

### Surface Printing (Overall)

#### Electrical Characteristics (Overall)

##### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

55.777

##### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

53.1522

##### Max. Operating Voltage - UL:

Voltage

300 V RMS

##### Max. Recommended Current:

Current

2.2 Amps per conductor @ 25°C

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5502UE 008C500	152 MT	2.948 KG	GRAY		4 #22 PP FRPVC
5502UE 008U1000	305 MT	6.804 KG	GRAY		4 #22 PP FRPVC
5502UE 008U500	152 MT	3.629 KG	GRAY		4 #22 PP FRPVC
5502UE 0081000	305 MT	6.804 KG	GRAY	C	4 #22 PP FRPVC
5502UE 009U1000	305 MT	6.804 KG	WHITE		4 #22 PP FRPVC
5502UE 0091000	305 MT	6.804 KG	WHITE	C	4 #22 PP FRPVC

#### Notes:

C = CRATE REEL PUT-UP.

## 5502UE Multi-Conductor - Commercial Applications

Revision Number: 2    Revision Date: 06-18-2012

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.