



Part Number: 70001LS

IDS SWA

Product Description

AWG18 (7xAWG26) tinned copper

Technical Specifications

Product Overview

Environmental Space:	Outdoor
Suitable Applications:	Instrumentation and computer cable; For data transmission applications; Profibus PA Cable

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
18	7x26	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
FPE - Foamed Polyethylene	2.5 mm	0.05 mm	0.65 mm

Color Chart

Number	Color
Pair 1	Red & Green

Inner Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Aluminum / Polyester		Tinned copper	AWG20/7
Braid	Tinned copper	85 %		

Inner Jacket Material

Material	Color	Nominal Diameter	Nominal Wall Thickness
FRNC / LSZH (UV stabilised)	Black or Blue	8 mm	1.15 mm

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	12.8 mm	0.3 mm	1.27 mm

Construction and Dimensions

Cabling

Description	Filler
1 pair and 2 fillers twisted to cable core	Polyethylene (2x) (1.65 mm)

Armor

Type of Armor	Material	Thickness of Armoring Wires	Coverage Percentage
Steel Wire Armoring	Galvanized steel wire	0.9 mm	Min. 95 %

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Outer Shield DCR
20.5 Ohm/km	9 Ohm/km

Capacitance

Max. Capacitance Conductor to Conductor	Max. Capacitance Unbalance
80 pF/m	4 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
0.03125 MHz	100 Ohm	20 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
0.039 MHz	0.3 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
77 %

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temp Range:	-15°C To +70°C
Storage Temp Range:	-45°C To +70°C
Operating Temp Range (Flexible Install):	-15°C To +70°C
Operating Temp Range (Fixed Install):	-45°C To +70°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Max Recommended Pulling Tension:	50 N
Min Bend Radius During Installation:	120 mm
Min Setting Radius:	80 mm

Standards

CENELEC Compliance:	EN 50290-2-27
Other Specification:	BS 7655 section 6.1 table 1, LTS 3

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-3-24
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color	Length
70001LS.001000	Black	1,000 m
70001LS.00120	Black	120 m
70001LS.00500	Black	500 m
70001LS.011000	Blue	1,000 m
70001LS.01500	Blue	500 m
70001LS.021000	Orange	1,000 m

History

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.