


Low Loss 50 Ohm Wireless RF Transmission Cable

RG-8X Type


Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

RG-8X Type • 15 AWG Solid .057" Bare Copper Conductor • Duobond® II (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)


Gas-injected Foam HDPE Insulation • Black Polyethylene Jacket

RF240 80°C	7808A	—	500	152.4	18.0	8.2	15 AWG (solid) .057" BC 3.2Ω/M' 10.5Ω/km	.150	3.81	Duobond II* + 95% TC Braid BC 2.8Ω/M' 9.2Ω/km	.240	6.10	50	86%	23.0	75.5	30	1.3	4.1
			1000	304.8	39.0	17.7											50	1.6	5.3
																			
100% Sweep tested. 6 GHz. Max. VSWR 1.25:1. Belden® The Wire in Wireless.																			
Mates with standard RG-8X connectors.** Suitable for Outdoor and Direct Burial applications.																			

Gas-injected Foam HDPE Insulation • Black PVC Jacket

RF240 80°C	7808R	NEC:	500	152.4	20.0	9.1	15 AWG (solid) .057" BC 3.2Ω/M' 10.5Ω/km	.150	3.81	Duobond II* + 95% TC Braid BC 2.8Ω/M' 9.2Ω/km	.240	6.10	50	86%	23.0	75.5	30	1.3	4.1
		CMR:	1000	304.8	44.0	20.0											50	1.6	5.3
		CEC:																	
		CMG FT4																	
																			
100% Sweep tested. 6 GHz. Max. VSWR 1.25:1. Belden® The Wire in Wireless.																			
Mates with standard RG-8X connectors.**																			

Gas-injected Foam HDPE Insulation • Flooded Water-resistant Black Polyethylene Jacket

RF240 80°C	7808WB	—	500	152.4	18.0	8.2	15 AWG (solid) .057" BC 3.2Ω/M' 10.5Ω/km	.150	3.81	Duobond II* + 95% TC Braid BC 2.8Ω/M' 9.2Ω/km	.240	6.10	50	86%	23.0	75.5	30	1.3	4.1
			1000	304.8	39.0	17.7											50	1.6	5.3
																			
100% Sweep tested. 6 GHz. Max. VSWR 1.25:1. Belden® The Wire in Wireless.																			
Mates with standard RG-8X connectors.** Suitable for Outdoor and Direct Burial applications.																			

BC = Bare Copper • DCR = DC Resistance • HDPE = High-density Polyethylene • TC = Tinned Copper

*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).

**Please consult Belden's website, www.belden.com, for complete listing.