

Broadband Coax

CATV Cables

Series 59

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation	
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.

Series 59 • 20 AWG Solid .032" Bare Copper-covered Steel Conductor • Duofoil® (100% Coverage) + TC Braid Shield(s) (96% Coverage)

Plenum • Foam FEP Teflon® Insulation • Black FEP Jacket

	200°C	89108	NEC:	500 [†]	152.4	17.0	7.7	20 AWG	.140	3.56	Duofoil	.203	5.16	75	82%	16.5	54.1	10	.7	2.3
			CATVP	1000 [†]	304.8	34.0	15.4	(solid)			+ 96%							50	1.8	5.9
			CMP					.032"			TC Braid							100	2.6	8.5
			CEC:					BCCS			2.6Ω/M'							200	3.7	12.1
			CMP					26.0Ω/M'			8.5Ω/km							400	5.4	17.7
								85.3Ω/km										700	7.3	24.0
																		900	8.4	27.6
																	1000	8.9	29.2	

Plenum • Foam FEP Teflon Insulation • Natural Flamarrest® Jacket

	75°C	82108	NEC:	U-1000 [†]	U-304.8	34.0	15.4	20 AWG	.140	3.56	Duofoil	.202	5.13	75	82%	16.5	54.1	10	.8	2.6
			CATVP	1000 [†]	304.8	32.0	14.5	(solid)			+ 96%							50	1.8	5.9
			CMP					.032"			TC Braid							100	2.6	8.5
			CEC:					BCCS			2.6Ω/M'							200	3.7	12.1
			CMP FT6, CXC FT4					26.0Ω/M'			8.5Ω/km							400	5.4	17.7
								85.3Ω/km										700	7.3	24.0
																		900	8.4	27.6
																	1000	8.9	29.2	

Plenum • Foam FEP Teflon Insulation • Snow Beige FEP Jacket

	200°C	1151A	NEC:	1000 [†]	304.8	40.0	18.2	20 AWG	.140	3.56	(2) Duofoil	.236	5.99	75	84%	16.5	54.1	10	.8	2.6
			CMP					(solid)			Shields							50	1.8	5.9
			CMP FT6					.032"			+ (2) TC							100	2.6	8.5
								BCCS			Braids							200	3.7	12.1
								26.0Ω/M'			2.3Ω/M'							400	5.4	17.7
								85.3Ω/km			7.5Ω/km							700	7.3	24.0
																		900	8.4	27.6
																	1000	8.9	29.2	

BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

[†]Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.

Teflon is a DuPont trademark.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com