

For more Information  
please call

1-800-Belden1



## General Description:

18 AWG solid .037" silver-coated copper-covered steel conductor, plenum, TFE Teflon® insulation, silver-coated copper braid shield (95% coverage), FEP jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	18	Solid	SCCCS - Silver-coated Copper-covered Steel	0.9398

Total Number of Conductors: 1

### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (mm)
Teflon®	TFE - Tetrafluoroethylene	2.9464

### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	SCC - Silver-coated Copper	95

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
FEP - Fluorinated Ethylene Propylene

### Overall Cable

Overall Nominal Diameter: 4.318 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

UL Temperature Rating: 200°C

Bulk Cable Weight: 44.646 Kg/Km

Max. Recommended Pulling Tension: 498.198 N

Min. Bend Radius/Minor Axis: 50.800 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2P

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-DTL-17, M17/111
RG Type:	303/U

### Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

#### Impedance (Ohm)

50

### Nom. Inductance:

#### Inductance (µH/m)

0.219827

### Nom. Capacitance Conductor to Shield:

#### Capacitance (pF/m)

95.149

### Nominal Velocity of Propagation:

#### VP (%)

70

### Nominal Delay:

#### Delay (ns/m)

4.85588

### Nom. Conductor DC Resistance:

#### DCR @ 20°C (Ohm/km)

53.4803

### Nominal Outer Shield DC Resistance:

#### DCR @ 20°C (Ohm/km)

14.1083

### Nom. Attenuation:

#### Freq. (MHz) Attenuation (dB/100m)

1	0.9843
10	3.6091
50	8.8587
100	12.7959
200	18.3736
400	26.9042
700	36.091
900	41.0125
1000	44.2935

### Max. Operating Voltage - UL:

#### Voltage

150 V RMS

### Max. Operating Voltage - Other:

#### Voltage Description

1400 V RMS	MIL
------------	-----

## Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
84303 0011000	1,000 FT	31.000 LB	BROWN	C E	RG303 COAX
84303 001500	500 FT	16.000 LB	BROWN	C E	RG303 COAX

**Notes:**

C = CRATE REEL PUT-UP.

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 4    Revision Date: 04-04-2014

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.