

**Industrial Data Solutions® – Industrial Data**

LonWorks Cables



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

**16 AWG • Stranded (19x29) 1.5 mm Tinned Copper • Twisted Pair**

**Polyethylene Insulation • Chrome FRNC/LSNH Jacket**


Part 1	<b>8471NH</b>	IEC 60332	1000	305	60.5	27.5	1.47 mm	0.105	2.67	Unshielded	0.280	7.10	Black, White
			1640	500	66.1	30.0	16 AWG						
			3280	1000	132.3	60.0	(19x29) TC						



1-Pair

**Polyethylene Insulation • FRNC/LSNH Inner Jacket • Steel Wire Armor • Chrome FRNC/LSNH Outer Jacket**

Part 1	<b>8471LS</b>	IEC 60332	1000	305	248.9	112.9	1.47 mm	0.032	0.81	Unshielded	0.413	10.50	Black, White
			1640	500	407.9	185.0	16 AWG						
			3280	1000	815.7	370.0	(19x29) TC						



1-Pair

**Tefzel® Insulation • Clear Tefzel® Jacket**

300V RMS 80° VW-1	<b>85102</b>		500	152	20.1	9.1	1.47 mm	0.015	0.38	Unshielded	0.211	5.36	Black, White
			1000	305	33.1	15.0	16 AWG (19x29) TC						



1-Pair

**16 AWG • Stranded (19x29) 1.5 mm Tinned Copper • Twisted Pair • Beldfoil® • 18 AWG Tinned Copper Drain Wire**

**Polyethylene Insulation • Chrome PVC Jacket**

300V RMS 80° UL AWM Style 20253 CM	<b>8719</b>	NEC: CM CL2 CEC: CM	U-500	U-152	24.5	11.1	1.47 mm	0.032	0.81	Overall Beldfoil® + Drain Wire (18 AWG TC)	0.313	7.95	Black, Clear
			500	152	24.5	11.1	16 AWG						
			U-1000	U-305	47.2	21.4	(19x29) TC						
			1000	305	49.2	22.3							
			2000	610	100.3	45.5							
			5000	1524	245.6	111.4							
10000	3049	431.0	195.5										



1-Pair

TC = Tinned Copper • DCR = DC resistance

Tefzel® is a DuPont trademark.