

# Plenum-Rated

## Unshielded


### Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

**22 AWG** Stranded (7x30) Tinned Copper Conductors • Conductors Cabled

**Plenum • FEP Insulation • Red FEP Jacket**


300V RMS	<b>88444</b>	NEC: CMP CEC: CMP FT6	4	Black, White, Red, Green	100 500 <sup>†</sup> 1000 <sup>†</sup>	30.5 152.4 304.8	2.9 9.0 15.0	1.3 4.1 6.8	.006 .15 .010	.15 .25	.121	3.07
----------	--------------	--------------------------------	---	-----------------------------------	--	------------------------	--------------------	-------------------	---------------------	------------	------	------



Suitable for Outdoor and Direct Burial applications.

**Plenum • FEP Insulation • Natural Flamarrest® Jacket**

300V RMS	<b>82444</b>	NEC: CMP CEC: CMP FT6	4	Black, White, Red, Green	U-500 <sup>†</sup> U-1000 <sup>†</sup> 1000 <sup>†</sup>	U-152.4 U-304.8 304.8	9.0 16.0 15.0	4.1 7.3 6.8	.006 .15	.015 .38	.134	3.40
----------	--------------	--------------------------------	---	-----------------------------------	--	-----------------------------	---------------------	-------------------	-------------	-------------	------	------



**22 AWG** Stranded (7x30) Tinned Copper Conductors • Twisted Pairs

**Plenum • FEP Insulation • Red FEP Jacket**


300V RMS	<b>88442</b>	NEC: CMP CEC: CMP FT6	2	Black, Red	100 500 <sup>†</sup> 1000 <sup>†</sup>	30.5 152.4 304.8	2.3 5.5 8.0	1.0 2.5 3.7	.006 .15	.012 .30	.102	2.59
----------	--------------	--------------------------------	---	---------------	--	------------------------	-------------------	-------------------	-------------	-------------	------	------



Suitable for Outdoor and Direct Burial applications.

**Plenum • FEP Insulation • Natural Flamarrest Jacket**

300V RMS	<b>82442</b>	NEC: CMP CEC: CMP FT6	2	Black, Red	U-1000 <sup>†</sup> 1000 <sup>†</sup>	U-304.8 304.8	9.0 8.0	4.1 3.7	.006 .15	.015 .38	.113	2.87
----------	--------------	--------------------------------	---	---------------	--	------------------	------------	------------	-------------	-------------	------	------



**18 AWG** Stranded (19x30) Tinned Copper Conductors • Conductors Cabled

**Plenum • FEP Insulation • Red FEP Jacket**


300V RMS	<b>88489</b>	NEC: CMP CEC: CMP FT6	4	Black, White, Red, Green	500 <sup>†</sup> 1000 <sup>†</sup>	152.4 304.8	14.5 29.0	6.6 13.2	.007 .18	.009 .23	.161	4.09
----------	--------------	--------------------------------	---	-----------------------------------	---------------------------------------	----------------	--------------	-------------	-------------	-------------	------	------



Suitable for Outdoor and Direct Burial applications.

**Plenum • FEP Insulation • Natural Flamarrest Jacket**

300V RMS	<b>82489</b>	NEC: CMP CEC: CMP FT6	4	Black, White, Red, Green	U-1000 <sup>†</sup> 1000 <sup>†</sup>	U-304.8 304.8	31.0 29.0	14.1 13.2	.007 .18	.014 .36	.170	4.32
----------	--------------	--------------------------------	---	-----------------------------------	--	------------------	--------------	--------------	-------------	-------------	------	------



<sup>†</sup>Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.

4 • Multi-Conductor Cables