

For more Information  
please call

1-800-Belden1



## Description:

RG-62/U type, 22 AWG solid .025" bare copper-covered steel conductor, plenum, semi-solid FEP insulation, bare copper braid shield (94% coverage), FEP jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	22	Solid	BCCS - Bare Copper Covered Steel	0.635

Total Number of Conductors: 1

### Insulation

#### Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (mm)
Teflon®	Semi-Solid FEP - Semi-Solid Fluorinated Ethylene-Propylene	3.6068

### Outer Shield

#### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	94

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
FEP - Fluorinated Ethylene Propylene

### Overall Cable

Overall Nominal Diameter: 5.080 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

UL Temperature Rating: 200°C

Bulk Cable Weight: 49.111 Kg/Km

Max. Recommended Pulling Tension: 373.649 N

Min. Bend Radius/Minor Axis: 63.500 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	62/U

### Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Burial:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9269

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

93

### Nom. Inductance:

Inductance (µH/m)

0.364191

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

41.9968

### Nominal Velocity of Propagation:

VP (%)

85

### Nominal Delay:

Delay (ns/m)

3.92736

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

135.177

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

11.1554

### Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100m)

1	0.9843
10	2.9529
50	6.2339
100	8.8587
200	12.4678
400	17.3893
700	23.9513
900	26.9042
1000	28.5447

### Max. Operating Voltage - UL:

Voltage

300 V RMS

## Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.[]

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89269 0091000	305 MT	15.422 KG	WHITE	C	#22 COAX FEP RG62A/U
89269 010100	30 MT	2.359 KG	BLACK		#22 COAX FEP RG62A/U
89269 0101000	305 MT	15.422 KG	BLACK	C	#22 COAX FEP RG62A/U
89269 010500	152 MT	8.165 KG	BLACK	C	#22 COAX FEP RG62A/U

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 05-14-2007

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.