


Multi-Conductor

Power and Control Cables

Description	Part No.	No. of Cond.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

SO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed

600V, 60°C • Conductors Cabled with Fillers • Paper Tape Separator • Color Code: See Chart 2 (Tech Info Section)

	9420	5	100	30.5	13.3	6.0	Black	16 (65x34) BC	.033	.84	.084	2.13	.506	12.85
			500	152.4	73.5	33.4								
			1000	304.8	143.0	65.0								
	9422	7	100	30.5	18.5	8.4	Black	16 (65x34) BC	.033	.84	.083	2.11	.581	14.76
			500	152.4	101.0	45.9								
			1000	304.8	201.0	91.4								
	9424	9	100	30.5	29.6	13.4	Black	16 (65x34) BC	.033	.84	.100	2.54	.720*	18.29
			500	152.4	150.5	68.4								
			1000	304.8	288.0	130.9								
9425	12	100	30.5	32.6	14.8	Black	16 (65x34) BC	.033	.84	.100	2.54	.720	18.29	
		500	152.4	165.5	75.2									
		1000	304.8	318.0	144.5									
9427	16	100	30.5	39.5	17.9	Black	16 (65x34) BC	.033	.84	.100	2.54	.787	19.99	
		500	152.4	194.5	89.3									
		1000	304.8	388.0	178.6									
9429	20	100	30.5	48.4	22.0	Black	16 (65x34) BC	.033	.84	.100	2.54	.862	21.89	
		500	152.4	233.0	105.9									
		1000	304.8	466.0	211.8									

BC = Bare Copper • CPE = Chlorinated Polyethylene
*Fillers added in the center.