

# Data sheet

ID	<b>FXKVR BK</b>
Description	double-walled ducting with draw-wire
Properties	corrugated exterior, smooth interior, including one coupler medium resistance against compression, normal impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	flame propagating
Classification	N 450, IP 40



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature  
-30 bis +70 °C

UV-Level  
L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
055 107	30 mm	40 mm	50 m	1400 m
041 925	41 mm	50 mm	50 m	-
032 332	52 mm	63 mm	50 m	-
026 353	61 mm	75 mm	50 m	-
041 343	75 mm	90 mm	50 m	-
041 344	95 mm	110 mm	50 m	-
041 990	107 mm	125 mm	50 m	-
042 514	136 mm	160 mm	25 m	-
099 585	170 mm	200 mm	25 m	-

## Further technical details

Details	
Model	Pliable
Shape	Outer side ribbed, inner side plain
Surface protection	Untreated
Transparent	False
Material	PE

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.