


Unshielded

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

22 AWG Stranded (7x30) Tinned Copper Conductors • Twisted Pairs

PVC Insulation • Chrome PVC Jacket														
 <p>UL AWM Style 2576 (150V 80°C)</p>	9744	NEC: CMG CEC: CMG FT4	2	See Chart 3 (Tech Info Section)	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	13.5 14.0 26.0 27.0	6.1 6.4 11.8 12.3	.010	.25	.032	.81	.244	6.20
	9745	NEC: CMG CEC: CMG FT4	3	See Chart 3 (Tech Info Section)	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	18.0 18.0 34.0 36.0	8.2 8.2 15.4 16.4	.010	.25	.032	.81	.257	6.53
	9746	NEC: CMG CEC: CMG FT4	4	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	22.5 42.0	10.2 19.1	.010	.25	.032	.81	.281	7.14
	8747	NEC: CMG CEC: CMG FT4	6	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.2 30.0 59.0	2.8 13.6 26.8	.010	.25	.035	.89	.320	8.13
	8748	NEC: CMG CEC: CMG FT4	9	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.6 43.5 84.0	3.9 19.8 38.2	.010	.25	.037	.94	.389	9.88
	9747	NEC: CMG CEC: CMG FT4	12	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	11.5 55.0 109.0	5.2 25.0 49.5	.010	.25	.040	1.02	.425	10.80
	8749	NEC: CMG CEC: CMG FT4	15	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	64.0 124.0	29.1 56.4	.010	.25	.040	1.02	.440	11.18
	9748	NEC: CMG CEC: CMG FT4	19	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	81.5 159.0	37.0 72.3	.010	.25	.040	1.02	.505	12.83
	8750	NEC: CMG CEC: CMG FT4	27	See Chart 3 (Tech Info Section)	1000 [†]	304.8	221.0	100.5	.010	.25	.045	1.14	.575	14.61

[†]Spools are one piece, but length may vary -0% to +20% from length shown.