


Data sheet

| | |
|-------------|---|
| ID | HFAFT/MBS BK |
| Description | adaptor with female thread and male bush, halogen-free |
| Properties | for the connection of rigid or pliable conduits with distribution and enclosure boxes |
| Colour | black, similar to RAL 9005 |



Working temperature
-25 to +90 °C

Degree of protection (IP)
IP54

| Art. no. | Nominal diameter | Thread connection size | Thread length | ps | pl |
|----------|------------------|------------------------|---------------|--------|---------|
| 009 673 | 16 mm | M16 x 1.5 | 11 mm | 100 pc | 2400 pc |
| 009 674 | 20 mm | M20 x 1.5 | 14 mm | 100 pc | 1200 pc |
| 009 675 | 25 mm | M25 x 1.5 | 14 mm | 50 pc | 600 pc |
| 009 676 | 32 mm | M32 x 1.5 | 14 mm | 20 pc | 480 pc |
| 009 677 | 40 mm | M40 x 1.5 | 14 mm | 25 pc | 300 pc |
| 009 678 | 50 mm | M50 x 1.5 | 16 mm | 10 pc | 120 pc |

Areas of Recommended Application

| Area | |
|--|-------|
| Approved in combination with protective conduit CSA | False |
| Approved in combination with protective conduit UR | False |
| Approved in combination with protective conduit DIN EN 61386-23 | True |
| Approved in combination with protective conduit Lloyd's Register | False |

Further technical details

| Details | |
|--------------------|--------------------|
| Model | Straight |
| Revolving thread | False |
| Construction type | Internal thread |
| Type of connection | Plug-in connection |
| Thread type | Metric |
| Material sealing | No sealing |
| Material | PC-Blend |