

For more Information  
please call

1-800-Belden1



## Description:

11 AWG stranded (7x19) .108" bare copper conductor, foam polyethylene insulation, double bare copper braid shield (96% coverage) polyethylene jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	11	7x19	BC - Bare Copper	2.7432

Total Number of Conductors: 1

### Insulation

#### Insulation Material:

Insulation Material	Dia. (mm)
FPE - Foam Polyethylene	7.239

### Inner Shield

#### Inner Shield Material:

Type	Inner Shield Material	Coverage (%)
Braid	BC - Bare Copper	96

### Inner Jacket

#### Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (mm)
PE - Polyethylene	9.398

### Outer Shield

#### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	96

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
PE - Polyethylene

### Overall Cable

Overall Nominal Diameter: 12.192 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -55°C To +80°C

Non-UL Temperature Rating: 80°C

Bulk Cable Weight: 193.466 Kg/Km

Max. Recommended Pulling Tension: 1450.110 N

Min. Bend Radius/Minor Axis: 127 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 8/U

## Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

50

### Nom. Inductance:

Inductance (µH/m)

0.213265

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

85.306

### Nominal Velocity of Propagation:

VP (%)

78

### Nominal Delay:

Delay (ns/m)

4.2653

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

3.9372

### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)

3.9372

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

6.8901

### Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100m)

1.000 0.328

10.000 1.641

50.000 3.937

100.000 5.906

200.000 8.859

400.000 13.780

700.000 19.030

900.000 21.983

1000.000 23.295

### Max. Operating Voltage - Non-UL:

Voltage

300 V RMS (Between shield)

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9888 0101000	305 MT	62.142 KG	BLACK	C	50 OHM TRIAX
9888 010500	152 MT	32.886 KG	BLACK	C	50 OHM TRIAX

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 04-06-2009

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.