


### Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-423 Applications

De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Nom. Vel. of Prop.	Nominal Capacitance		Color Code	
			ft.	m	lbs.	kg		inch	mm		inch	mm		pF/ft.	pF/m		
<b>24 AWG • Stranded Conductors (7x32) 0.6 mm Tinned Copper • Overall Beldfoil® Shield + 65% Tinned Copper Braid • 24 AWG TC Drain Wire</b> <b>Datalene® Insulation • Chrome PVC Jacket</b>																	
30V 80°C UL AWM Style 2919		NEC: CM CEC: CM					0.61 mm 24 AWG (7x32) TC	0.053	1.35	Overall Beldfoil® + Overall 65% TC Braid + Drain Wire (24 AWG TC)			78%				
																	
	<b>9925</b>	3 CDR	100 500 1000	31 152 305	3.5 12.1 24.0	1.6 5.5 10.9					0.215	5.46		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9927</b>	4 CDR	100 500 1000	31 152 305	3.5 14.6 32.0	1.6 6.6 14.5					0.230	5.84		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9929</b>	5 CDR	100 500 1000	31 152 305	4.0 16.1 35.9	1.8 7.3 16.3					0.246	6.25		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9931</b>	6 CDR	100 500 1000 10000	31 152 305 3048	4.2 17.6 39.0 410.3	1.9 8.0 17.7 186.1					0.265	6.73		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9932</b>	7 CDR	100 500 1000	31 152 305	4.4 18.5 41.0	2.0 8.4 18.6					0.265	6.73		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9633</b>	8 CDR	100 500 1000 10000	31 152 305 3048	4.9 21.2 46.1 480.4	2.2 9.6 20.9 217.9					0.280	7.11		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9934</b>	9 CDR	100 500 1000	31 152 305	5.3 22.0 48.1	2.4 10.0 21.8					0.300	7.62		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9935</b>	10 CDR	100 500 1000	31 152 305	5.7 28.0 53.1	2.6 12.7 24.1					0.306	7.77		CDR/CDR CDR/SCR	12 22	39 72	see chart 1 (Tech Info Section)
	<b>9636</b>	15 CDR	100 500 1000	31 152 305	7.3 35.1 68.1	3.3 15.9 30.9					0.350	8.89		CDR/CDR CDR/SCR	12 22	39 72	see chart 2R (Tech Info Section)
	<b>9937</b>	25 CDR	100 500 1000	31 152 305	9.9 54.7 108.0	4.5 24.8 49.0					0.445	11.30		CDR/CDR CDR/SCR	12 22	39 72	see chart 2R (Tech Info Section)
	<b>9938</b>	37 CDR	100 500 1000	31 152 305	13.0 71.6 139.1	5.9 32.5 63.1					0.500	12.70		CDR/CDR CDR/SCR	12 22	39 72	see chart 2R (Tech Info Section)

TC = Tinned Copper • DCR = DC resistance • SCR = Capacitance between one conductor and other conductors connected to shield. • CDR = Capacitance between conductors