



# Individually Shielded

## Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/Ft.	* pF/m	** pF/Ft.	** pF/m
<b>24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire</b>																		
<b>Polyethylene Insulation • Chrome PVC Jacket</b>																		
 <p>UL AWM Style 2919 (30V 80°C)</p>	<b>9990</b>	NEC: 3 CM CEC: CM	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	16.0 36.0	7.3 16.4	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.255 6.48	60	66%	25	82	47	154		
	<b>9991</b>	NEC: 6 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.7 32.5 62.0	3.1 14.7 28.3	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.330 8.38	60	66%	25	82	47	154		
	<b>9992</b>	NEC: 9 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.8 42.5 86.0	4.0 19.3 39.1	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.383 9.73	60	66%	25	82	47	154		
	<b>9993</b>	NEC: 12 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	9.8 107.0 48.6	4.5 21.2 52.7	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.428 10.87	60	66%	25	82	47	154		
	<b>9995</b>	NEC: 25 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	21.2 116.0 228.0	9.7 52.7 103.6	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.636 16.15	60	66%	25	82	47	154		

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/Ft.	* pF/m	** pF/Ft.	** pF/m
<b>22 AWG Solid Conductors • TC • Twisted Pairs • Individually Shielded w/ Beldfoil (100% Coverage) • 22 AWG Solid TC Drain Wire</b>																		
<b>PVC Insulation • Overall Chrome PVC Jacket</b>																		
 <p>UL AWM Style 2464 (300V 80°C)</p>	<b>8767</b>	NEC: 3 MPG, CMG CEC: MPG, CMG FT4	See Chart 3 (Tech Info Section)	U-500 U-1000	U-152.4 304.8	22.5 46.0	10.3 21.0	.013 .33	.33 .037	.037 .94	.279 7.10	40	131	77	253			
	<b>8768</b>	NEC: 6 MPG, CMG CEC: MPG, CMG FT4	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	46.5 92.0	21.1 41.8	.013 .33	.037 .94	.379 9.60	40	131	77	253				
	<b>8764</b>	NEC: 9 MPG, CMG CEC: MPG, CMG FT4	See Chart 3 (Tech Info Section)	1000	304.8	122.0	55.5	.013 .33	.040 1.02	.425 10.80	40	131	77	253				
	<b>8765</b>	NEC: 11 MPG, CMG CEC: MPG, CMG FT4	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	76.5 149.0	34.8 67.7	.013 .33	.040 1.02	.470 11.90	40	131	77	253				
	<b>8766</b>	NEC: 15 MPG, CMG CEC: MPG, CMG FT4	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	101.5 196.0	46.1 89.1	.013 .33	.045 1.14	.525 13.30	40	131	77	253				

DCR = DC Resistance • TC = Tinned Copper

\* Capacitance between conductors.

\*\* Capacitance between one conductor and other conductors connected to shield.