


AX100045 Faceplates and Panels - FiberExpress Front Cover 1U



For more Information
please call

1-800-Belden1

General Description:

FiberExpress Front Cover for Patch Panel, Rack Mount, 1U, Smoked Lexan

Usage (Overall)

Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room
Related Parts:	FiberExpress Adapter Strips, Fiber Splice Organizer Trays and Kits, Offset Bracket Kit, Right Side Cable Entry Bracket

Physical Characteristics (Connectivity)

Capacity

Access

Termination Area:	Front Swing Out
--------------------------	-----------------

Dimensions

Dimensions:

Height (mm)	Width (mm)	Depth (mm)
41.910	342.900	105.410

Materials

Materials:

Description	Material
Front Cover	Lexan
Latch	Thermo-Plastic

Weight

Weight:	0.454 kg
----------------	----------

Included Parts

Included Parts:	Identification Label; Installation Sheet
------------------------	--

Packaging

Packaging:	Individually packaged in a cardboard box.
-------------------	---

Mechanical Characteristics (Connectivity)

Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C
Operating Temperature Range:	-10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor:	Yes
------------------------------	-----

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For proper installation refer to Installation Guide PX100104 included with the product or visit our web site at <http://www.belden.com>

Product Family

Part Numbers:

Description	Item Number
FiberExpress Rack Mount PP 1U Black	AX100041
FiberExpress Rack Mount PP 2U Black	AX100068
FiberExpress Rack Mount PP 3U Black	AX104934
FiberExpress Rack Mount PP 4U Black	AX100116

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100045	1 EA	1.002 LB			FIBEREXPRESS 12/24 PORT

AX100045 Faceplates and Panels - FiberExpress Front Cover 1U

Revision Number: 0 Revision Date: 02-24-2012

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.