


Data sheet

ID	HGL BK
Description	gland with flange, halogen-free
Colour	black, similar to RAL 9005



Working temperature
-45 to +150 °C

Degree of protection (IP)
IP54

Art. no.	Nominal diameter	Thread connection size	Thread length	Total length	Small Package	Large Package
012 753	16 mm	M16 x 1.5	10,5 mm	18,9 mm	100 pc	1600 pc
011 790	20 mm	M20 x 1.5	12 mm	24 mm	50 pc	1200 pc
012 609	25 mm	M25 x 1.5	15 mm	30,4 mm	50 pc	600 pc
012 754	32 mm	M32 x 1.5	15 mm	32 mm	30 pc	360 pc
015 507	40 mm	M40 x 1.5	15 mm	38 mm	20 pc	240 pc
015 506	50 mm	M50 x 1.5	15 mm	42,4 mm	16 pc	128 pc
026 933	63 mm	M63 x 1.5	20 mm	54 mm	8 pc	64 pc

Areas of Recommended Application

Area	
Approved in combination with protective conduit CSA	False
Approved in combination with protective conduit UR	False
Approved in combination with protective conduit VD TÜV/GGVS	False
Approved in combination with protective conduit DIN EN 61386-23	False
Approved in combination with protective conduit Lloyd's Register	False

Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	External thread
Type of connection	Other
Thread type	Metric
Material sealing	No sealing
Material	PPO