

## Krabice do dut ch st n, PP, samozh šiv 

**HWDD**, vestavn  krabice pro dvojit  p stroje podle  esk ch a slovensk ch norem; oranov  (RAL 2004), rozte  s roub  60mm, poadovan  montzn  otvor  $\varnothing$  68mm, vn jší obruba krabice  $\varnothing$  73mm, pro desky tl. 7-35mm, max. p poejenn  4 hadic  $\varnothing$  20mm a 2 kabel 

Shoda s normami: IEC/EN 60670



materi�l	IP	tepl. rozsah		
PP	3X	-25�C/+75�C		
typ	rozm�r	mb	vb	ref.�.
HWDD 65	$\varnothing$ 65mm, 45mm	25	200	083 711

## Krabice do dut ch podkladov, PP, samozh šav 

**HWDD**, vstavann  krabica pre dvojn sobn  p stroje podl   esk ch a slovensk ch noriem; oranov  (RAL 2004), vzdialenos  skrutiek 60mm, potrebn  intala n  otvor  $\varnothing$  68mm, vonkaj lem krabice  $\varnothing$  73mm, pre podklady hrub  7-35mm, max. pripoejenie 4 ochrann ch r rokov  $\varnothing$  20mm a 2 k blov

Zhoda s normami: IEC/EN 60670

**HWDS**, krabice do n bytku; oranov  (RAL 2004), rozte  s roub  60mm, poadovan  montzn  otvor  $\varnothing$  68mm, vn j obruba krabice  $\varnothing$  71mm, pro desky tl. 7-35mm, max. p poejenn  4 hadic  $\varnothing$  20mm a 2 kabel 

Shoda s normami: IEC/EN 60670



materi�l	IP	tepl. rozsah		
PP	3X	-25�C/+75�C		
typ	rozm�r	mb	vb	ref.�.
HWDS 65	$\varnothing$ 65mm, 40mm	25	200	026 982

**HWDS**, krabica do n bytku; oranov  (RAL 2004), vzdialenos  skrutiek 60mm, potrebn  intala n  otvor  $\varnothing$  68mm, vonkaj lem krabice  $\varnothing$  71mm, pre podklady hrub  7-35mm, max. pripoejenie 4 ochrann ch r rokov  $\varnothing$  20mm a 2 k blov

Zhoda s normami: IEC/EN 60670

NEW

**HWDW**, p strojov  krabice; oranov  (RAL 2004), rozte  s roub  60mm, poadovan  montzn  otvor  $\varnothing$  68mm, vn j obruba krabice  $\varnothing$  71mm, pro desky tl. 7-35mm, max. p poejenn  4 hadic  $\varnothing$  20mm a 2 kabel , ide ln  pro instalace v pasivn ch domech

Shoda s normami: IEC/EN 60670



materi�l	IP	tepl. rozsah		
PP	3X	-25�C/+75�C		
typ	rozm�r	mb	vb	ref.�.
HWDW 65	$\varnothing$ 65mm, 45mm	25	200	100 109

**HWDW**, p strojov  krabica; oranov  (RAL 2004), vzdialenos  skrutiek 60mm, potrebn  intala n  otvor  $\varnothing$  68mm, vonkaj lem krabice  $\varnothing$  71mm, pre podklady hrub  7-35mm, max. pripoejenie 4 ochrann ch r rokov  $\varnothing$  20mm a 2 k blov, ide ln  pre intala cie v pasivn ch domoch

Zhoda s normami: IEC/EN 60670