


Data sheet

ID	KSR 3M
Description	plain ducting
Properties	rigid ducting, plain, with moulded-on coupler medium compression resistance, normal impact resistance
Colour	black/grey
Fire Behaviour	non flame propagating
Classification	N 450



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Length	Operating temperature	UV-Level
3 m	-5 bis +60 °C	L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
106 235	46,2 mm	50 mm	3 m	1419 m
106 236	58,6 mm	63 mm	3 m	891 m
106 237	69,9 mm	75 mm	3 m	654 m
106 238	84,2 mm	90 mm	3 m	414 m
106 239	103,4 mm	110 mm	3 m	285 m
106 240	117,6 mm	125 mm	3 m	204 m
106 241	150,6 mm	160 mm	3 m	117 m

Further technical details

Details	
Model	Rigid
Shape	Outer - and inner side plain
Surface protection	Untreated
Transparent	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.