


Part Number: H1000C1

COAX RF H1000 PE



Product Description

COAX RF [2.6/7.1] H1000 PE

Technical Specifications

Product Overview

Environmental Space:	Outdoor
Suitable Applications:	Coaxial cables used for Radio-Frequency designed according the International Standard IEC 1196

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
10	Solid	BC - Bare Copper	2.62 mm	0.03 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	7.15 mm	0.2 mm

Insulation, Table Note:	Centricity min. 85%
-------------------------	---------------------

Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Copper - Polyester		2 mm			
Braid	2	BC - Bare Copper	49 %		7.8 mm	0.25 mm	5 %

Outer Jacket Material

Material	Nominal Diameter	Diameter - Tolerance
PE - Polyethylene	10.3 mm	0.3 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

Construction and Dimensions

Min Elongation at Breakof Jacket:	300 %
Min Tensile Strength of Jacket:	10 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
3.5 Ohm/km	15.5 Ohm/1000ft	12 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
80 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
----------------------------------	----------------------------------	-------------------------

50 Ohm	2 Ohm	Min. 46 dB
--------	-------	------------

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	0.8 dB/100m
50 MHz	2.8 dB/100m
100 MHz	4 dB/100m
200 MHz	5.7 dB/100m
400 MHz	8.4 dB/100m
600 MHz	10.5 dB/100m
800 MHz	12.3 dB/100m
1000 MHz	14 dB/100m
1350 MHz	16.7 dB/100m
1750 MHz	19.5 dB/100m
2150 MHz	22.1 dB/100m
2400 MHz	23.6 dB/100m
5000 MHz	37.4 dB/100m
10000 MHz	59.3 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
83 %	2 %

Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	90 dB

Voltage

Voltage Test Dielectric
3.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-60°C To +70°C
Operating Temp Range:	-60°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	100 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	41-410 N at 50 mm N

Standards

ISO/IEC Compliance:	IEC 1196
RG Type:	8/U Type

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Part Number

Variants

Item #	Color	Length
H1000C1.001000	Black	1,000 m
H1000C1.00500	Black	500 m
H1000C1.009999	Black	1,000 m
H1000C1.01500	Black	500 m
H1000C1.00100	Black	100 m
H1000C1.K01000	Black	1,000 m

History

Update and Revision:	Revision Number: 0.144 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.