


Product: [H1001C2](#) 

COAX RF H1001 PVC



## Product Description

COAX RF [2.6/7.1] H1001 STRANDED PVC

## Technical Specifications

### Product Overview

Environmental Space:	Indoor/Outdoor
Suitable Applications:	Coaxial cables used for Radio-Frequency designed according the International Standard IEC 1196

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
10	Stranded	BC - Bare Copper	19x0.54 mm	2.7 mm	0.05 mm	1

Conductor Count:	1
------------------	---

#### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	7.15 mm	0.2 mm

Insulation, Table Note:	Centricity min. 85%
-------------------------	---------------------

#### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Copper - Polyester		2 mm			
Braid	2	BC - Bare Copper	49 %		7.9 mm	0.25 mm	5 %

#### Outer Jacket Material

Material	Nominal Diameter	Diameter - Tolerance
PVC - Polyvinyl Chloride	10.3 mm	0.3 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

### Construction and Dimensions

Min Elongation at Breakof Jacket:	300 %
Min Tensile Strength of Jacket:	10 MPa

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
4.5 Ohm/km	16.5 Ohm/1000ft	12 Ohm/km

#### Capacitance

Nom. Capacitance	Capacitance Tolerance
80 pF/m	3 pF/m

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance

50 Ohm	2 Ohm	Min. 46 dB
--------	-------	------------

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1 dB/100m
50 MHz	3.3 dB/100m
100 MHz	4.7 dB/100m
200 MHz	6.7 dB/100m
400 MHz	9.8 dB/100m
600 MHz	12.2 dB/100m
800 MHz	14.4 dB/100m
1000 MHz	16.3 dB/100m
1350 MHz	19.3 dB/100m
1750 MHz	22.5 dB/100m
2150 MHz	25.4 dB/100m
2400 MHz	27.1 dB/100m
5000 MHz	42.4 dB/100m
10000 MHz	66.4 dB/100m

#### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
83 %	2 %

#### Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	100 dB

#### Voltage

Voltage Test Dielectric
3.0 kV DC

#### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-25°C To +70°C
Operating Temp Range:	-25°C To +70°C

#### Mechanical Characteristics

Bulk Cable Weight:	127 kg/km
Min Bend Radius (W/o Pulling Strength):	100 mm
Crush Resistance:	Max. 1% (load of 700N) N

#### Standards

ISO/IEC Compliance:	IEC 1196
RG Type:	8/U Type

#### Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

#### Flammability, LS0H, Toxicity Testing

Burning Load:	1600 kJ/m
---------------	-----------

#### Part Number

#### Variants

Item #	Color	Length
H1001C2.00500	Black	500 m

#### History

Update and Revision:	Revision Number: 0.152 Revision Date: 01-31-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.