


Part Number: H126D00

COAX H126 DUOBONDPLUS PVC



Product Description

COAX [1.0/4.6] H126 DUOBONDPLUS PVC

Technical Specifications

Product Overview

Environmental Space:	Indoor/Outdoor
Suitable Applications:	Coaxial cables used in cabled distribution networks designed according to the European Standard EN 50117; Operating at frequencies between 5 MHz and 3000 MHz; The International Standard IEC 1196

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1 mm	0.03 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	4.57 mm	0.15 mm

Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape, bonded to dielectric	1	Aluminum/Polyester/Aluminum		1 mm			
Braid	2	TC - Tinned Copper	35 %		5.4 mm	0.2 mm	5 %
Tape, (L-folded) bonded to sheath	3	Aluminum/Polyester		1 mm			

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	6.9 mm	0.2 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
23 Ohm/km	39 Ohm/1000ft	16 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
54 pF/m	2 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1.8 dB/100m
50 MHz	4.7 dB/100m
100 MHz	6.5 dB/100m
200 MHz	9.8 dB/100m
400 MHz	13 dB/100m
600 MHz	16.2 dB/100m
800 MHz	18.7 dB/100m
1000 MHz	21.1 dB/100m
1350 MHz	24.9 dB/100m
1750 MHz	28.8 dB/100m
2150 MHz	32.3 dB/100m
2400 MHz	34.4 dB/100m
3000 MHz	39.2 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
82 %	2 %

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 470 MHz	20 dB
470 - 1000 MHz	18 dB
1000 - 2000 MHz	16 dB
2000 - 3000 MHz	15 dB

High Freq Table Note: In each frequency band, 3 peak values up to 4 dB lower are allowed

Screening

Frequency [MHz]	Min. Screening Attenuation After Flexing
30 - 1000 MHz	95 dB
1000 - 2000 MHz	85 dB
2000 - 3000 MHz	75 dB

Voltage

Voltage Test Dielectric
2.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	35 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	No shrinkback N
Adhesion Jacket:	50 N at 200 mm

Standards

ISO/IEC Compliance:	IEC 1196
CENELEC Compliance:	EN 50117 and EN 50117-1
RG Type:	6/U Type

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Part Number

Variants

Item #	Color	Length
H126D00.021000	Black	1,000 m
H126D00.00250	White	250 m
H126D00.00500	White	500 m
H126D00.00B100	White	100 m
H126D00.00U250	White	250 m
H126D00.011000	White	1,000 m

History

Update and Revision:	Revision Number: 0.149 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.