


**Part Number: H12B00**

**COAX H12 PVC CATV**



**Product Description**

COAX H12 PVC CATV

**Technical Specifications**

[Product Overview](#)

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Coaxial cables used in cabled distribution networks designed according to the European Standard EN 50117; Operating at frequencies between 5 MHz and 2150 MHz; The International Standard IEC 1196

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
24	Stranded	BC - Bare Copper	7x0.20 mm	0.6 in	0.02 mm	1

Conductor Count: 1

**Insulation**

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Polyethylene	3.5 mm	0.15 mm

**Outer Shield Material**

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	BC - Bare Copper	90 %	4.05 mm	0.15 mm	5 %

**Outer Jacket Material**

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	5.6 mm	0.3 mm

OuterJacket1, Table Note: According to European Standard HD 624

**Construction and Dimensions**

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

**Electrical Characteristics**

**Conductor DCR**

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
80 Ohm/km	92.5 Ohm/1000ft	12.5 Ohm/km

**Capacitance**

Nom. Capacitance	Capacitance Tolerance
67 pF/m	2 pF/m

**Impedance**

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	2.9 dB/100m
50 MHz	9.4 dB/100m
100 MHz	13.3 dB/100m
200 MHz	19 dB/100m
400 MHz	27.2 dB/100m
600 MHz	33.7 dB/100m
800 MHz	39.2 dB/100m
1000 MHz	44.1 dB/100m
1350 MHz	51.7 dB/100m
1600 MHz	56.7 dB/100m
1750 MHz	59.5 dB/100m
2150 MHz	66.5 dB/100m
2400 MHz	70.6 dB/100m

### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
66 %	2 %

### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	20 dB
30 - 470 MHz	20 dB
470 - 862 MHz	18 dB
862 - 2150 MHz	16 dB

High Freq Table Note: In each frequency band, 3 peak values up to 4 dB lower are allowed

### Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	50 dB

### Voltage

Voltage Test Dielectric
2.0 kV DC

### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-15°C To +70°C
Operating Temp Range:	-15°C To +70°C

### Mechanical Characteristics

Torsion Test: Min Number of Torsions:	100000
Torsion Test: Description:	PMS XN-039131
Min Bend Radius (W/o Pulling Strength):	25 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	4.7-47 N at 25 mm N

### Standards

ISO/IEC Compliance:	IEC 1196
CPR Euroclass:	Eca
CENELEC Compliance:	EN 50117 and EN 50117-1
RG Type:	Mini 59/U Type

### Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

### Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

## Part Number

---

### Variants

Item #	Color	Length
H12B00.012000	Beige	2,000 m
H12B00.01500	Beige	500 m
H12B00.01B100	Beige	100 m
H12B00.022000	Beige	2,000 m
H12B00.02B100	Beige	100 m
H12B00.00500	Black	500 m
H12B00.00B100	Black	100 m
H12B00.00B200	Black	200 m

### History

Update and Revision:	Revision Number: 0.148 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.