



Part Number: H155A02
COAX RF H155 FRNC

Product Description

COAX RF [1.4/3.9] H155 STRANDED FRNC

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Dca
Suitable Applications:	50 Ohm low loss coaxial transmission cable designed according European Standard EN 50117-1; Operating Frequencies between 5 and 6000 MHZ

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
16	Stranded	BC - Bare Copper	19x0.28 mm	1.41 mm	0.03 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	3.9 mm	0.15 mm

Insulation, Table Note:	Centricity min. 85%
-------------------------	---------------------

Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Aluminum/Polyester/Aluminum		2 mm			
Braid	2	TC - Tinned Copper	80 %		4.5 mm	0.25 mm	5 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC	5.4 mm	0.2 mm

Construction and Dimensions

Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
15.4 Ohm/km	32.4 Ohm/1000ft	17 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
84 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	2.5 dB/100m
50 MHz	6.9 dB/100m
100 MHz	9.1 dB/100m
230 MHz	13.4 dB/100m
400 MHz	18 dB/100m
800 MHz	26.1 dB/100m
862 MHz	27.3 dB/100m
1000 MHz	29.6 dB/100m
1350 MHz	34.9 dB/100m
1750 MHz	40.3 dB/100m
2150 MHz	46 dB/100m
2400 MHz	49.1 dB/100m
3000 MHz	56.3 dB/100m
3600 MHz	62.9 dB/100m
4200 MHz	69.1 dB/100m
4800 MHz	75.1 dB/100m
5400 MHz	80.8 dB/100m
6000 MHz	86.5 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
80 %	2 %

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	20 dB
30 - 470 MHz	20 dB
470 - 1000 MHz	18 dB
1000 - 2000 MHz	16 dB
2000 - 3000 MHz	15 dB
3000 - 6000 MHz	15 dB

High Freq Table Note: In each frequency band, 3 peak values up to 4 dB lower are allowed, values above 3000 MHz for information only

Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	85 dB

Voltage

Voltage Test Dielectric
2.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

Mechanical Characteristics

Max Recommended Pulling Tension:	100 N
Min Bend Radius (W/o Pulling Strength):	60 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	5-50 N at 25 mm N

Standards

CPR Euroclass:	Dca-s1,d1,a1
CENELEC Compliance:	EN 50117-1, EN 50117-2-4 and EN 50290-2-20
RG Type:	58/U Type

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2013-02-19
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
Other Flammability:	UN ECE R118.02
Amount of Halogen acc. to IEC 60754-1 & EN50267-1: Zero	

Part Number

Variants

Item #	Color	Length
H155A02.001010	Black	1,010 m
H155A02.00505	Black	505 m

History

Update and Revision:	Revision Number: 0.154 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.