


Part Number: MRG1791
COAX RG179 PVC



Product Description

COAX [0.3/1.6] RG179 STRANDED PVC

Technical Specifications

Product Overview

Environmental Space:	Indoor/Outdoor
Suitable Applications:	Coaxial communication cable based on MIL-C-17

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
30	Stranded	SPCCS - Silver Plated Copper Covered Steel	7x0.10 mm	0.3 mm	0.02 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Polyethylene	1.6 mm	0.15 mm

Outer Shield Material

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	TC - Tinned Copper	85 %	2 mm	0.15 mm	4 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	2.8 mm	0.1 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

Electrical Characteristics

Conductor DCR

Max. Conductor DCR
802 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
67 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
10 MHz	15 dB/100m

100 MHz	27 dB/100m
1000 MHz	85 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
66 %

Voltage

Voltage Rating [V]
2000 DC / 1000 V RMS

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-25°C To +70°C
Operating Temp Range:	-25°C To +70°C

Standards

CPR Euroclass:	Fca
RG Type:	179/U Type
MIL Spec Rating:	MIL-C-17

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2005-11-17
---------------------------------------	------------

Part Number

Variants

Item #	Color	Length
MRG1791.00100	Black	100 m
MRG1791.0050	Black	50 m
MRG1791.00150	Black	150 m

History

Update and Revision:	Revision Number: 0.145 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.