



Fig. 1:  
ecobus® Combi Adapter-S  
5 x Power + Bus



Fig. 2:  
ecobus® Combi Adapter-S  
5 x Power



Fig. 3:  
ecobus® Combi Adapter-S  
Bus

## Product information

### Application

For permanently connecting the ecobus® Combi cable in dry areas without the need to remove cable sheathing.

### General Properties

Housing	Polyamide 6,6, light grey
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Power current screw	Silver-plated brass, for posidrive no. 2 screwdriver
Bus screw	Galvanised brass, for normal no. 2 screwdriver
Test Specifications	IEC 60998-1, IEC 60998-2-3
Housing	Flammability according to UL Standard 94: V-2
Slider and Cap	Flammability according to UL Standard 94: V-0
	Halogen-free
Slider	Glass-fibre: 25%

See Fig. 1: ecobus® Combi Adapter-S

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	$n \times \text{mm}^2 + n \times \text{mm}^2$	g/unit	app. mm	kWh/unit	pcs.
1300 235	$5 \times 2,5 + 2 \times 1,5$	86	76 x 41 x 39	0,471	50

See Fig. 2: ecobus® Combi Adapter-S

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	$n \times \text{mm}^2$	g/unit	app. mm	kWh/unit	pcs.
1300 236	$5 \times 2,5$	60	53 x 41 x 39	0,329	50

See Fig. 3: ecobus® Combi Adapter-S

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	$n \times \text{mm}^2$	g/unit	app. mm	kWh/unit	pcs.
1300 237	$2 \times 1,5$	27	21 x 41 x 36	0,138	50