

## ecobus® Combi Adapter

Flat cable sockets  
with plugable connection  
Bus output



Fig. 1:  
ecobus® Combi Adapter EIB



Fig. 2:  
ecobus® Combi Adapter  
Bus

### Product information

#### Application

For permanently connecting the ecobus® Combi cable in dry areas without the need to remove cable sheathing.

#### General Properties

Housing	Flammability according to UL Standard 94: V-2
Slider and Cap	Flammability according to UL Standard 94: V-0
	Halogen-free
Slider	Glass-fibre: 25%
Connection	Output on side with confusion-free jacks
Housing	Polyamide 6,6
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Bus screw	Galvanised brass, for normal no. 2 screwdriver
Test Specifications	EIB/KNX Manual

#### Further Information

correct plugs for 1300 285 see page E-32  
correct plugs for 1300 352 see page E-32

See Fig. 1: ecobus® Combi Adapter EIB/KNX / colour green

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm	g/unit	app. mm	kWh/unit	pcs.
1300 285	2 x 0,8	18	54 x 27 x 25,7	0,12	50

See Fig. 2: ecobus® Combi Adapter / colour light grey

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm	g/unit	app. mm	kWh/unit	pcs.
1300 352	2 x 0,8	18	54 x 27 x 25,7	0,12	50