


Type 8800-Z

**Product information**



<b>Application</b>	Compensation weight for internal and panoramic elevators	
<b>Installation</b>	To comply with the correct installation procedures please refer to the installation manual which is available separately	
<b>Construction</b>	Weight elements	heavy weight compound
	Electrical elements	none
	Steel supporting members	Ø 4 - 6mm
	Outer sheath	PVC
<b>Mechanical properties</b>	Free suspension length:	approx. 125 m, other length on request
	Running speed:	≤ 2.5 m/s <sup>2</sup>
	Acceleration:	≤ 1.2 m/s <sup>2</sup>
	Operating temperature:	-15 to +70 °C
	Loop diameter:	according to table
<b>Suspension device</b>	LZ 4001	
<b>Colour code</b>	Outer sheath:	grey
<b>Standard</b>	 EN 50214	

**Type 8800-Z**

Part no.	Product code	Cable weight approx.		Overall dimensions approx. [w x t] [mm x mm]	Diameter of steel supporting members [mm]	loop [mm]
		[kg/m]	[lbs/ft]			
182 268	CW-STD 1.1	1.1	0.75	12.6 x 43.0	4.0	400
181 651	CW-STD 1.5	1.5	1.0	14.0 x 53.0	4.0	450
181 652	CW-STD 2.2	2.2	1.5	14.0 x 74.0	4.0	450
181 653	CW-STD 3.0	3.0	2.0	14.0 x 96.0	5.0	450
181 654	CW-STD 3.7	3.7	2.5	16.0 x 104.0	5.0	550
181 655	CW-STD 4.5	4.5	3.0	18.0 x 112.0	6.0	650
181 656	CW-STD 5.2	5.2	3.5	19.0 x 121.0	6.0	700
181 657	CW-STD 6.0	6.0	4.0	20.0 x 133.0	6.0	750