



unilan® RJ45 Module MU 1/8 Cat.6 unshielded



Parallel pliers for easy termination

## Product information

### Application

#### unilan® RJ45 Module MU 1/8 Cat.6 unshielded

For the transmission of digital and analogue voice, video and data signals. Especially suitable for all Class E applications according to ISO/IEC 11801:2002, EN 50173-1: 2002 and EIA/TIA 568-B.2-1.

### Description

Easy termination PCB with IDC terminations modules with integrated strain relief (cable tie, not included) High component density possible owing to the very small module dimension

#### Information:

All faceplates and surface mount boxes as for shielded MS-Modules are suitable!

### Mechanical properties

Diameter wire solid	0.40 mm (AWG 26) to 0.65 mm (AWG 22)
Diameter wire stranded	AWG26/7 bare stranded copper wire with 7 strands for AWG 22, AWG 23 and AWG 24 when using a wire with the same or bigger cross section.
Reusable	
Diameter over insulation	0.70 mm to 1.40 mm (1.60 mm)
Temperature range	Storage: -40°C to +70°C Installation: -10°C to +60°C In use: -10°C to +60°C

### Standards

IEC 60603-7-4 (250 MHz unshielded)  
ISO/IEC 11801:2002  
TIA/EIA 568 B.2-1

### General Characteristics

Colour code for wire termination according to T568-A (usual) and T568-B is clearly marked on cable manager.

■ Cat./Class                      Cat 6, Class E

Article No.	Description	Colour	PU
185 750	unilan® RJ45 Module MU 1/8 Cat.6, unshielded, colour code T568-A	white	10 pieces
185 751	unilan® RJ45 Module MU 1/8 Cat.6, unshielded, colour code T568-B	white	10 pieces