


Data sheet

ID	VE BK
Description	straight gland
Properties	suitable for UFX
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating



Working temperature	Degree of protection (IP)	UV-Level
-15 to +60 °C	IP65	L2

Art. no.	Nominal diameter	Thread connection size	Thread length	Small Package	Large Package
005 550	16 mm	M16 x 1.5	12,5 mm	25 pc	-
005 551	20 mm	M20 x 1.5	13,5 mm	25 pc	-
005 540	21 mm	PG21	18 mm	25 pc	-
005 541	29 mm	PG29	18 mm	10 pc	-
005 553	32 mm	M32 x 1.5	18 mm	5 pc	-
036 759	40 mm	M40 x 1.5		5 pc	-
037 369	50 mm	M50 x 1.5		10 pc	-

Areas of Recommended Application

Area	
Approved in combination with protective conduit CSA	False
Approved in combination with protective conduit UR	False
Approved in combination with protective conduit VD TÜV/GGVS	False
Approved in combination with protective conduit DIN EN 61386-23	False
Approved in combination with protective conduit Lloyd's Register	False

Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Material sealing	Other
Material	PP

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.