

## Firestop systems



End coated mineral fibre plate MFP



Identification sign

## PRODUCT INFORMATION

### APPLICATION

Used to form a bulkhead for cable wall and ceiling penetration against the effects of fire for a period of 90 minutes in accordance with DIN 4102-9 (fire resistance class S90/S120).

Article No.	Bulkhead	Application	Info
1300 464	Mineral fibre plate pyroplast-S 100 P	For provision of a S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Single-side end coated Set consists of 5 plates (Dimensions: 5 x 0.3 m <sup>2</sup> ) in box = 1.5 m <sup>2</sup>
301 371	Fire protection paint pyroplast-S 100 D	For coating mineral-fibre plates and technical cables on bulkhead exit	15 kg plastic bucket white, with carry handle water-based, solvent free
301 370	Fire protection filler pyroplast-S 100 SM	For closing gaps and cracks and wall soffits	5 kg plastic bucket, white, with carry handle water-based, solvent free
1300 467	Fire protection filler pyroplast-S 100 SM-K	For finishing off gaps and cracks and wall soffits	310 ml cartridge, white Set consists of 12 cartridges water-based, solvent free
1300 478	Identification sign for flat bulkhead	For permanent identification of a cable bulkhead in accordance with DIN 4102-9	Set consists of 10 identification signs