

Class D / Cat. 5e - unshielded

Data cable Cat.5e

- Cu-Data Cable up to 100 MHz 4x2xAWG24 for structured premises cabling
- applicable from ISDN to 1000 Base-T
- Applicable standards: EN 50173-1:2002, ISO/IEC 11801:2002/A2:2010

U/UTP



uninet® 502 4P U/UTP AWG24

Article No.	Dimension n x n x mm (AWG)	Sheath	Sheath • mm	Weight kg/km	Cu weight kg/km	Fire load kWh/m	MJ/m	Colour	PU
382 980	4 x 2 x 0,51 (AWG24)	FR/PVC ¹⁾	5,5	33,6	18,1	0,14	0,49	grey RAL 7037	305m Box
182 980	4 x 2 x 0,51 (AWG24)	FR/PVC ¹⁾	5,5	33,6	18,1	0,14	0,49	grey RAL 7037	1000m Drum
382 981	4 x 2 x 0,51 (AWG24)	FRNC/LSOH ²⁾	5,5	33,8	18,1	0,12	0,43	grey RAL 7037	305m Box
182 981	4 x 2 x 0,51 (AWG24)	FRNC/LSOH ²⁾	5,5	33,8	18,1	0,12	0,43	grey RAL 7037	1000m Drum

¹⁾ FR/PVC = Flame Retardant/Polyvinylchloride

²⁾ FRNC/LSOH = Flame Retardant Non Corrosive/Low Smoke Zero Halogen

unilan® Modules

RJ45 Modules unshielded Cat.5e



KU-T 1/8 Cat. 5e, unshielded tool-less



KU 1/8 Cat. 5e, unshielded



Insertion Tool 110



unilan® Keystone Hand Puck

Article No.	Description	Colour	PU
418 072	RJ45 Keystone KU-T 1/8 Cat. 5e unshielded, Tool-less	white	10 pieces
418 073	RJ45 Keystone KU-T 1/8 Cat. 5e unshielded, Tool-less	black	10 pieces
418 082	RJ45 Keystone KU 1/8 Cat. 5e unshielded	white	10 pieces
418 083	RJ45 Keystone KU 1/8 Cat. 5e unshielded	black	10 pieces
185 896	Insertion Tool 110 (recommended for RJ45 Keystone modules)		1 piece
185 898	unilan® Keystone Hand Puck, installation aid for RJ45 Keystone modules	red	1 piece