

FIBRE OPTIC PANELS & ENCLOSURES

FO patch panel OV-A / OV-AT

19"/2U, unloaded

exchangeable front plate, extractable,
depth-adjustable mounting



Fibre optic patch panel OV-AT, 19"/2U, without front plate, extractable, depth-adjustable mounting

PRODUCT INFORMATION

APPLICATION For the termination of fibre optic cables (breakout, loose tube) - maximum of 96 fibres. Applicable with a wide range of front plates / connector systems (see OV-A / OV-AT 2U accessories).

CONSTRUCTION

Housing:	metallic, extractable drawer (OV-A) or drawer with telescopic slides (OV-AT), both with locking mechanism
Rack mounting:	depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour (variants):	similar to RAL 7035 or stainless steel
Imprint:	numbers (silk screen printing) on frontplate (to be ordered separately)
Capacity:	up to 96 fibres
Strain relief:	with cable tie and screwed cable gland or cable distributor
Cable entry:	rear left and right
Dimensions:	19"/2U, depth 254 mm

CONNECTOR SYSTEM Adapter: ST, FC, SCD, SC, LSH, LCD

SCOPE OF DELIVERY Box, strain relief with M25 (2U) cable gland, splice tray holder and adhesive fibre fixation (3 pcs.)

Please order the front plate separately.

Article No.	Description	Colour (similar to)	Note
416960	OV-A extractable 2U	RAL 7035	without front plate
416965	OV-AT telescopic 2U	RAL 7035	without front plate
416977	OV-AT telescopic 2U	Stainless steel	without front plate
416959	Telescopic slides for upgrading OV-A to OV-AT		
418098	Label for OV-A and OV-AT, aluminium, length 420 mm		

Copper

Fibre Optics

Cabinets & Racks

Data Centre

Wireless

Multimedia

General Information

FO-Panel OV-A, OV-AT_2HE0712/e