

Data outlet CSD 2/8-K flush duct mounted with 2 RJ45-Jacks Cat.6/E_A shielded



Fig. 1:
unilan® data outlet
CSD 2/8-K Cat.6/E_A
(incl. central plate)



Fig. 2:
unilan® data outlet
CSD 2/8-K Cat.6/E_A



Fig. 3:
unilan® central plate
50 x 50 mm



Fig. 4:
unilan® cover frame
80 x 80 mm

Product information

Application

unilan® data outlet CSD 2/8-K Cat.6/E_A shielded, angled

For the transmission of digital and analogue voice-, video- and data signals. The outlet is specified up to 500 MHz. In connection with data cables Cat.7 or 7_A all applications of class D, E and EA can be supported, that is including 10 Gigabit Ethernet in compliance with IEEE 802.3an. The data outlet is primarily intended for flush channel mounted. The construction is compatible with all named design-faceplate supplier.

Construction

Housing: Solid metal, die cast zinc, mounting clip optional detachable
Dimensions: 70 x 70 x 47 mm (incl. central plate)
Boards: Base board with two LSA plus connector blocks
Outlet module fitted with one or two RJ45 sockets
Screen tap: 360° via metal wedge
Strain relief: 4-way cable entry via metal wedge
Cable entry from 4 directions with two cables possible



Connection System

Cable LSA-plus punch down contacts, AWG 26-22

Applicable standards

ISO/IEC 60603-7-5
ISO/IEC 11801:2002 / Amd.1:2008 (class E_A)
EN 50173:2007
TIA/EIA 568-B.2-10:2008
EN 55022

General properties

EMC Shielded
Cat/Class Cat 6, Class E_A

Article No.	Fig.	Description	Colour (similar)	PU
417 960	1	unilan® data outlet CSD 2/8-K Cat.6/E _A (incl. central plate)	pure white RAL 9010	1
417 961	1	unilan® data outlet CSD 2/8-K Cat.6/E _A (incl. central plate)	oyster white RAL 1013	1
417 962	2	unilan® data outlet CSD 2/8-K Cat.6/E _A		1
417 975	3	unilan® data outlet CSD 2/8 central plate 50x50mm	pure white RAL 9010	10
417 976	3	unilan® data outlet CSD 2/8 central plate 50x50mm	oyster white RAL 1013	10
417 977	3	unilan® data outlet CSD 2/8 central plate 50x50mm	black RAL 9005	10
1400 830	4	unilan® data outlet CSD 2/8 cover frame 80x80mm	pure white RAL 9010	10
1401 630	4	unilan® data outlet CSD 2/8 cover frame 80x80mm	oyster white RAL 1013	10

Accessories

Article No.	Description
1401 609	LSA-plus termination tool for LSA punch down contacts
	Assembly holders for mounting of outlets in the cable ducts

Additional assembly tools / accessories can be found under System Accessories.