

Class E_A / Cat. 6_A - shielded

For more information and products please visit www.datwyler.com

Data cable Cat. 6_A

- Cu-Data cable up to 500 MHz 4x2xAWG23 for structured premises cabling
- applicable up to 10GBase-T
- Applicable standards: EN 50173-1:2002, ISO/IEC 11801:2002/A2:2010

S/FTP



F/FTP



U/FTP



7060 4P S/FTP AWG23

Article No.	Dimension	Sheath	Sheath Ø	Weight	Cu weight	Fire load	Colour	PU
	n x n x mm (AWG)		mm	kg/km	kg/km	kWh/m MJ/m		
182 924	4 x 2 x 0,55 (AWG23)	FRNC/LS S0H ¹⁾	7,1	55,0	26,4	0,152 0,55	orange RAL 2003	1000m Drum

6552 4P F/FTP AWG23

Article No.	Dimension	Sheath	Sheath Ø	Weight	Cu weight	Fire load	Colour	PU
	n x n x mm (AWG)		mm	kg/km	kg/km	kWh/m MJ/m		
191 454	4 x 2 x 0,55 (AWG23)	FRNC/LS S0H ¹⁾	7,0	48,5	20,0	0,14 0,52	orange RAL 2003	1000m Drum

6502 4P U/FTP AWG23

Article No.	Dimension	Sheath	Sheath Ø	Weight	Cu weight	Fire load	Colour	PU
	n x n x mm (AWG)		mm	kg/km	kg/km	kWh/m MJ/m		
191 453	4 x 2 x 0,55 (AWG23)	FRNC/LS S0H ¹⁾	7,0	47,8	20,0	0,15 0,55	orange RAL 2003	1000m Drum

¹⁾ FRNC/LS0H = Flame Retardant Non Corrosive/Low Smoke Zero Halogen

Module



RJ45 Module shielded Cat. 6_A/E_A

Article No.	Description	Colour	PU
418 061	Module KS-T 6 _A 1/8 (IEC) Tool-less Cat. 6 _A /E _A shielded	metallic	10 pieces

For compatible patch panels - page 15 faceplates and accessories - page 17