



## DESCRIPTION

Semi tight buffer, 900  $\mu$ m  
Colours single pigtails: turquoise  
Colours sets of pigtails: in accordance with IEC 60304

## OPTICAL PROPERTIES

Ferrule material:	Zirkonia
Lifetime:	1000 connections with stable attenuation values
Reproducibility of the IL:	maximal +/- 0.1dB
Testing method IL:	IEC 61300-3-4
Testing method RL:	IEC 61300-3-6
Connector grade (better than):	Bm2m
Insertion loss (IL), typical	0.15 dB
Insertion loss (IL), maximal:	0.3 dB
Return loss (RL), typical:	35 dB
Return loss (RL), minimal:	30 dB

## VERSIONS

Article No.	Product	Connector type	Fibre type	PU
421141	Fibre Pigtail	SC	G50/125 OM3	1 pc.
421142	Fibre Pigtail	SC	G50/125 OM3	1 set
422242	Fibre Pigtail	ST	G50/125 OM3	1 set
422241	Fibre Pigtail	ST	G50/125 OM3	1 pc.
423341	Fibre Pigtail	LC	G50/125 OM3	1 pc.
423342	Fibre Pigtail	LC	G50/125 OM3	1 set
424441	Fibre Pigtail	LSH	G50/125 OM3	1 pc.
424442	Fibre Pigtail	LSH	G50/125 OM3	1 set
425541	Fibre Pigtail	FC/PC	G50/125 OM3	1 pc.
425542	Fibre Pigtail	FC/PC	G50/125 OM3	1 set