



DESCRIPTION

Semi tight buffer, 900 µm
Colours single pigtails: orange
Colours sets of pigtails: in accordance with IEC 60304

OPTICAL PROPERTIES

Ferrule material:	Zirkonia
Lifetime:	1000 connections with stable attenuation values
Reproducibility of the IL:	maximal +/- 0.1dB
Testing method IL:	IEC 61300-3-4
Testing method RL:	IEC 61300-3-6
Connector grade (better than):	Bm2m
Insertion loss (IL), typical	0.15 dB
Insertion loss (IL), maximal:	0.3 dB
Return loss (RL), typical:	35 dB
Return loss (RL), minimal:	30 dB

VERSIONS

Article No.	Product	Connector type	Fibre type	PU
421161	Fibre Pigtail	SC	G50/125 OM2	1 pc.
421162	Fibre Pigtail	SC	G50/125 OM2	1 set
422261	Fibre Pigtail	ST	G50/125 OM2	1 pc.
422262	Fibre Pigtail	ST	G50/125 OM2	1 set
423361	Fibre Pigtail	LC	G50/125 OM2	1 pc.
423362	Fibre Pigtail	LC	G50/125 OM2	1 set
424461	Fibre Pigtail	LSH	G50/125 OM2	1 pc.
424462	Fibre Pigtail	LSH	G50/125 OM2	1 set
425561	Fibre Pigtail	FC/PC	G50/125 OM2	1 pc.
425562	Fibre Pigtail	FC/PC	G50/125 OM2	1 set