



DESCRIPTION

Semi tight buffer, 900 µm
Colours single pigtails: yellow
Colours sets of pigtails: in accordance with IEC 60304

OPTICAL PROPERTIES

| | |
|--------------------------------|---|
| Ferrule material: | Zirkonia |
| Lifetime: | 1000 connections with stable attenuation values |
| Reproducibility of the IL: | maximal +/- 0.1dB |
| Testing method IL: | IEC 61300-3-4 |
| Testing method RL: | IEC 61300-3-6 |
| Connector grade (better than): | B2 |
| Insertion loss (IL), typical | 0.12 dB |
| Insertion loss (IL), maximal: | 0.25 dB |
| Return loss (RL), typical: | 55 dB |
| Return loss (RL), minimal: | 50 dB |

VERSIONS

| Article No. | Product | Connector type | Fibre type | PU |
|-------------|---------------|----------------|--------------------|-------|
| 421121 | Fibre Pigtail | SC | E9/125 G.652.D OS2 | 1 pc. |
| 421122 | Fibre Pigtail | SC | E9/125 G.652.D OS2 | 1 set |
| 422221 | Fibre Pigtail | ST | E9/125 G.652.D OS2 | 1 pc. |
| 422222 | Fibre Pigtail | ST | E9/125 G.652.D OS2 | 1 set |
| 423321 | Fibre Pigtail | LC | E9/125 G.652.D OS2 | 1 pc. |
| 423322 | Fibre Pigtail | LC | E9/125 G.652.D OS2 | 1 set |
| 424421 | Fibre Pigtail | LSH | E9/125 G.652.D OS2 | 1 pc. |
| 424422 | Fibre Pigtail | LSH | E9/125 G.652.D OS2 | 1 set |
| 425521 | Fibre Pigtail | FC/PC | E9/125 G.652.D OS2 | 1 pc. |
| 425522 | Fibre Pigtail | FC/PC | E9/125 G.652.D OS2 | 1 set |