



DESCRIPTION

Semi tight buffer, 900 µm
Colours single pigtails: yellow
Colours sets of pigtails: in accordance with IEC 60304

OPTICAL PROPERTIES

Ferrule material:	Zirkonia
Lifetime:	1000 connections with stable attenuation values
Reproducibility of the IL:	maximal +/- 0.1dB
Testing method IL:	IEC 61300-3-4
Testing method RL:	IEC 61300-3-6
Connector grade (better than):	B1
Insertion loss (IL), typical	0.12 dB
Insertion loss (IL), maximal:	0.25 dB
Return loss (RL), typical:	70 dB
Return loss (RL), minimal:	65 dB

VERSIONS

Article No.	Product	Connector type	Fibre type	PU
427721	Fibre Pigtail	SC/APC	E9/125 G.652.D OS2	1 pc.
427722	Fibre Pigtail	SC/APC	E9/125 G.652.D OS2	1 set
429921	Fibre Pigtail	LC/APC	E9/125 G.652.D OS2	1 pc.
429922	Fibre Pigtail	LC/APC	E9/125 G.652.D OS2	1 set
428821	Fibre Pigtail	LSH/APC	E9/125 G.652.D OS2	1 pc.
428822	Fibre Pigtail	LSH/APC	E9/125 G.652.D OS2	1 set