



Product information FMN alpha DSL WTM HS A

Industrial Ethernet:Wide Area Networking (ADSL, UMTS):FMN alpha DSL WTM HS A

<http://e-catalog.hirschmann.com/link/57078-24455-164217-164218/en/conf/ui/state>

Name	FMN alpha DSL WTM HS A
	
	ADSL modem from FMN communications GmbH
Delivery informations	
Availability	available
Product description	
Description	ADSL modem from FMN communications GmbH
Modi	ADSL modem
Port type and quantity	DSL access: ITU G.992.1 Annex A Ethernet interface: 10/100BaseT
Type	FMN alpha DSL WTM HS A
Order No.	942 043-001
More Interfaces	
Power supply/signaling contact	1 x terminal block, 4-pin
V.24 interface	n/a
USB interface	n/a
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Power requirements	
Operating voltage DC	10 V ... 60 V
Power consumption	13 W
Service	
Diagnostics	LEDs (power, DSL synchronisation, LAN data transfer)
Other services	ADSL2+ max. 24 Mbps (Downstream), ADSL2 max. 12 Mbps (Downstream), ADSL max. 8 Mbps (Downstream), up to 1 Mbps (Upstream)
Ambient conditions	
Operating temperature	-25 °C ... 55 °C
Mechanical construction	
Dimensions (W x H x D)	49 mm x 105 mm x 146 mm
Mounting	DIN Rail
Protection class	IP20
Scope of delivery and accessories	
Scope of delivery	device, terminal block, operating instructions

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.