



SPIDER Series Unmanaged DIN Rail Mount Switches

All Copper/RJ45		
Part No.	Order No.	Ports
SPIDER 3TX-TAP	943 899-001	3 x RJ45
SPIDER 5TX	943 824-002	5 x RJ45
SPIDER 5TX EEC	943 824-102	5 x RJ45
SPIDER II 8TX	943 957-001	8 x RJ45
SPIDER II 8TX EEC	943 958-001	8 x RJ45
SPIDER II 8TX POE	942 008-001	8 x RJ45 and 4 X PoE, with metal housing and 24 V DC input



All Copper/RJ45 and FIBER		
Part No.	Order No.	Ports
SPIDER 1TX/1FX	943 890-001	1 x RJ45 and 1 x MM, SC
SPIDER 1TX/1FX EEC	943 927-101	1 x RJ45 and 1 x MM, SC
SPIDER 1TX/1FX-SM	943 891-001	1 x RJ45 and 1 x MM, SC
SPIDER 1TX/1FX SM EEC	943 928-001	1 x RJ45 and 1 x SM, SC
SPIDER 4TX/1FX	943 221-001	4 x RJ45 and 1 x MM, SC
SPIDER 4TX/1FX EEC	943 221-101	4 x RJ45 and 1 x MM, SC
SPIDER 4TX/1FX-ST EEC	943 914-001	4 x RJ45 and 1 x MM, ST
SPIDER 4TX/1FX SM EEC	943 880-001	4 x RJ45 and 1 x SM, SC
SPIDER II 8TX/1FX EEC	943 958-111	8 x RJ45 and 1 x MM, SC
SPIDER II 8TX/1FX-ST EEC	943 958-121	8 x RJ45 and 1 x MM, ST
SPIDER II 8TX/2FX EEC	943 958-211	8 x RJ45 and 2 x MM, SC
SPIDER II 8TX/2FX-ST EEC	943 958-221	8 x RJ45 and 2 x MM, ST
SPIDER II 8TX/1FX-SM EEC	943 958-131	8 x RJ45 and 1 x SM, SC
SPIDER II 8TX/2FX-SM EEC	943 958-231	8 x RJ45 and 2 x SM, SC

FAST Ethernet Switches via PoE		
Part No.	Order No.	Ports
SPIDER 5TX PD EEC	942 051-001	5 x 10/100BaseTX Ports, one of which is 1 x PoE PD integrated port
SPIDER 1TX/1FX-MM PD EEC	942 051-002	1 x 10/100BaseTX PoE PD Port and 1 x 100BaseFX multimode SC
SPIDER 1TX/1FX-SM PD EEC	942 051-003	1 x 10/100BaseTX PoE PD Port and 1 x 100BaseFX singlemode SC

FULL GIGABIT		
Part No.	Order No.	Ports
SPIDER II Giga 5T EEC	943 962-002	5 x RJ45 (10/100/1000)
SPIDER II Giga 5T/2S EEC	943 963-002	5 x RJ45 (10/100/1000) and 2 x SFP Socket (1000)
SPIDER II Giga 5T EEC Pro	943 962-102	5 x RJ45 (10/100/1000), QoS support IEEE 802.1D
SPIDER II Giga 5T/2S EEC Pro	943 963-102	5 x RJ45 (10/100/1000) and 2 x SFP Socket (1000), QoS support IEEE802.1D
SPIDER II Giga 5T EEC Jumbo	943 962-202	5 x RJ45 (10/100/1000), Jumbo Frame support with up to 9014 Byte user data
SPIDER II Giga 5T/2S EEC Jumbo	943 963-202	5 x RJ45 (10/100/1000) and 2 x SFP Socket (1000), Jumbo Frame support with up to 9014 Byte user data

NOTE: EEC stands for extended environmental conditions (-40°C to +70°C).