



Product: [BE43769](#)

RailTuff Cat 5e, PROFINET, AWG 22 (19)

[Request Sample](#)

Product Description

RailTuff Railway Approved Cat 5e, PROFINET, AWG 22(19), HiFlex, Premium Cross-linked LSNH Insulation and Jacket, Heavy Shielded, DIN 5510-2 level 1 to 4, EN 50155 Flame Resistance acc EN 45545-2, IEC 60332-1-2, EN 50305 & IEC 60332-3-25 cat D, EN 45545-2 (Class R15 and R16 HL3), Oil Resistance

Technical Specifications

Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	No. of Conductors
22	Stranded	TC - Tinned Copper	19x0.15 mm	4

Table Notes:	IEC 60228 class 5
Conductor Count:	4
Total Number of Pairs:	2

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
PO - Polyolefin	1.63 mm	0.05 mm

Bonded-Pair:	No
--------------	----

Color Chart

Number	Color
Quad 1	White & Blue & Yellow & Orange

Inner Jacket Material

Material	Nominal Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	4.3 mm

Table Notes:	Bedding
--------------	---------

Outer Shield Material

Type	Material	Thickness of Foil	Min. Coverage [%]
Tape	Bi-Laminate (Alum+Poly)	50 / 23 µm	
Braid	Tinned Copper (TC)		80%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Min. Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.7 mm	0.3 mm	0.8 mm

Table Notes:	e-Beamed to Cross-link
--------------	------------------------

Electrical Characteristics

Conductor DCR

Max. Conductor DCR

57.1 Ohm/km

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
1 - 100	100 Ohm	15 Ohm

Delay

Max. Delay	Nominal Velocity of Propagation (VP) [%]
530 ns/100m	66%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. FEXT
1 MHz	2.1 dB/100m	65.3 dB	64 dB
4 MHz	4.1 dB/100m	56.3 dB	52 dB
10 MHz	6.5 dB/100m	50 dB	43.8 dB
16 MHz	8.3 dB/100m	47 dB	40 dB
31.25 MHz	11.7 dB/100m	42.9 dB	33.9 dB
62.5 MHz	17 dB/100m	38.4 dB	28 dB
100 MHz	22 dB/100m	35.3 dB	24 dB

Table Notes:	IEC 60288-2-2 and ISO/IEC 11801 ed. 2.0, Cat. 5e
General Electrical Parameters Notes:	IEC 60288-2-2 and ISO/IEC 11801 ed. 2.0, Cat. 5e

Transfer Impedance

Frequency [MHz]	Transfer Impedance
10 Mhz	Max. 10 mOhm/m

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +90°C
Operating Temp Range:	-40°C To +90°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Bulk Cable Weight:	68 kg/km
Min Bend Radius (W/o Pulling Strength):	67 mm
Min Setting Radius:	33.5 mm
No Adherence Wire to Wire/Wire to Jacket:	No adherence

Standards

GENELEC Compliance:	EN 45545-2 Hazard Level HL1-HL3
Data Category:	Category 5e
Other Specification:	EN 50306 par 4.8 + 4.9 + 4.10 (1.5 kV/1min); Toxicity index to NF X70-100 CITc Max. 0.7; EN45545-2 (Class R14 HL 3)

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-25
Fire Resistance (Time to Failure) Compliance:	DIN 5510-2 protection level 1 to 4
Other Flammability:	EN45545-2:2013 HL1 to HL 3 ; EN 50305 9.1.1 ; UN ECE-R118.02
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	10 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
BE43769.00305	Black	Reel	305 m	8719605026507
BE43769.00500	Black	Reel	500 m	8719605026514

History

Update and Revision:	Revision Number: 0.215 Revision Date: 05-11-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.