








Auto-Configuration Adapter – ACA

The ACA storage mediums enable managed switches, firewalls and wireless access points to be easily commissioned and quickly replaced. The following operations are supported:

- Transferring the current configuration data from an Ethernet device to the ACA storage medium
- Transferring the configuration data from the ACA storage medium to an Ethernet device
- Updating the software of an Ethernet device

	Product Name	Order Number	Description
	ACA11-RJ11 EEC	943 751-002	Auto-configuration adapter, with RJ11 RS232 interface and extended temperature ranges
	ACA11-M12 EEC	943 972-001	Auto-configuration adapter, with M12 interface and extended temperature range
	ACA21-USB EEC	943 271-003	Auto-configuration adapter 512 MB, with USB 1.1 connection and extended temperature range
	ACA21-M12 EEC	943 913-003	Auto-configuration adapter 64 MB, with M12 (USB 1.1) interface and extended temperature range
	ACA22-USB EEC	942 124-001	Auto-configuration adapter 512 MB, with USB 2.0 connection and extended temperature range
	ACA22A-USB Mini	942 152-001	Cordless Auto-configuration adapter 512 MB with USB 2.0 connection
	ACA22-M12 EEC	942 125-001	Auto-configuration adapter 512 MB, with M12 (USB 2.0) interface and extended temperature range
	ACA22-M12 EEC (right-angled)	942 125-002	Auto-configuration adapter 512 MB, with M12 (USB 2.0) interface and extended temperature range, right-angled
	ACA31	942 074-001	Auto-configuration adapter, SD card with 512 MB, extended temperature range
	Adapter Cable, M12-5pin to USB	942 199-001	Adapter cable to transfer files between an auto-configuration adapter (ACA21-M12 EEC or ACA22-M12 EEC) and a computer. Side A: M12 "A"-coded 5-pin socket Side B: USB A-Type connector

Supported Auto-configuration Adapters

Product Family	ACA11-RJ11 EEC	ACA11-M12 EEC	ACA21-M12 EEC	ACA21-USB EEC	ACA22A-USB Mini	ACA22-M12 EEC	ACA22-M12 EEC (right-angled)	ACA22-USB EEC	ACA31
SPIDER III PL				X	X			X	
OCTOPUS 8TX			X			X	X		
RSB	X								
RS20/30/40	X*			X	X			X	
RSR				X	X			X	
MS20/30	X*			X	X			X	
MSP30									X
MSP40					X			X	X
RED				X	X			X	
RSP/RSPL/RSPS									X
RSPE				X	X			X	X
MACH100				X	X			X	
MACH1000				X	X			X	
MACH4000				X	X			X	
GRS1020/1030				X	X			X	
GRS1040					X			X	X
OCTOPUS		X**	X			X	X		
OCTOPUS II			X			X	X		
EagleOne				X					
EAGLE20/30								X	X
OpenBAT-R				X				X	
OpenBAT-F			X			X	X		
BAT450-F		X							

*limited write support

**ACA only supported by 942 025-005/-006/-007/-008