




Product information OZD Profi 12M P11

Fiber Interfaces:Fieldbus Repeater:Profibus LWL-Repeater:OZD Profi 12M P11

<http://e-catalog.hirschmann.com/link/57078-57141-57128-57129-38151/en/conf/ustate>

Name	OZD Profi 12M P11
	
	interface converter electrical/optical for PROFIBUS-field bus networks; repeater function; for plastic FO; short-haul version; approval for Ex-zone 2 (Class 1, Div. 2)
Delivery informations	
Availability	available
Product description	
Description	interface converter electrical/optical for PROFIBUS-field bus networks; repeater function; for plastic FO; short-haul version; approval for Ex-zone 2 (Class 1, Div. 2)
Port type and quantity	1 x optical: 2 sockets BFOC 2.5 (STR); 1 x electrical: Sub-D 9-pin, female, pin assignment according to EN 50170 part 1
Type	OZD Profi 12M P11
Order No.	943 728-221
Electrical interface	
Signal type	PROFIBUS (DP-V0, DP-V1, DP-V2 und FMS)
Bit rate	9.6; 19.2; 45.45; 93.75; 187.5; 500 kbit/s; 1.5; 3; 6; 12 Mbit/s (automatic setting)
Signal delay time (optional input/output)	<= 6.5 bit times
Input/output signal	RS 485 level
Input voltage range	-7 V ... +12 V
Galvanic isolation	no
Optical interface	
Wavelength	660 nm
Cascadability	not limited
More interfaces	
Power supply	5-pin terminal block, screw mounting
Signaling contact	5-pin terminal block, screw mounting
Measuring outputs "Optical input power"	2 mm sockets
Network size - length of cable	
Single mode fiber (SM) 9/125 µm	-
Multimode fiber (MM) 50/125 µm	-
Multimode fiber (MM) 62.5/125 µm	-
Multimode fiber HCS (MM) 200/230 µm	400 m 8 dB link budget at 660 nm and transmitting power default A = 8 dB/km, 2 dB reserve
Multimode fiber POF (MM) 980/1000 µm	50 m 15 dB link budget at 660 nm and transmitting power reduced 80 m 20 dB link budget at 660 nm and transmitting power default A = 0.2 dB/m, 2 dB reserve
Power requirements	
Operating voltage	18 ... 32 VDC, typ. 24 VDC
Galvanic isolation	yes
Current consumption	max. 200 mA
Power consumption	4.8 W
Output voltage/output current (pin6)	5 VDC +5%, -10%, short circuit-proof/90 mA
Redundancy	
Redundancy functions	redundant 24 V infeed



Fiber Interfaces:Fieldbus Repeater:Profibus LWL-Repeater:OZD Profi 12M P11

<http://e-catalog.hirschmann.com/link/57078-57141-57128-57129-38151/en/conf/uistate>

Ambient conditions

Operating temperature 0 °C to +60 °C

Storage/transport temperature -40 °C to +70 °C

Relative humidity <95% (non-condensing)

Mechanical construction

Dimensions (W x H x D) 40 x 140 x 77.5 mm

Mounting DIN rail or mounting plate

Weight 500 g

Protection class IP 40

Housing material die-cast zinc

Approvals

Hazardous locations ATEX 100a, Zone 2

Issued or requested approvals FM Class 1, Div. 2; C-Tick

Scope of delivery and accessories

Scope of delivery device, 2 optical BFOC ST plugs, start-up instructions

Accessories to order separately manual, order no. 039 629-001

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.