




Product information Fast Ethernet MICE Media Modules, PoE - MM22-T1T1T1T1SAHH

Industrial Ethernet:Archive - Industrial Ethernet:Modular Industrial Switches:Configurable media modules:Fast Ethernet MICE media modules:Fast Ethernet MICE Media Modules, PoE

<http://e-catalog.hirschmann.com/link/57078-24455-49814-49860-67478-80931-252402/en/MM22-T1T1T1T1SAHH/uistate>

Name	Fast Ethernet MICE Media Modules, PoE
	
	Fast Ethernet media module for MICE Switches (MS...), supportive of Power over Ethernet, IEEE 802.3af
Delivery informations	
Availability	no longer available
Product description	
Description	Fast Ethernet media module for MICE Switches (MS...), supportive of Power over Ethernet, IEEE 802.3af
Port type and quantity	Port 1: 10/100BASE-TX, RJ45; Port 2: 10/100BASE-TX, RJ45; Port 3: 10/100BASE-TX, RJ45; Port 4: 10/100BASE-TX, RJ45
Type	MM22-T1T1T1T1SAHH
Order No.	MM22-T1T1T1T1SAHH
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Multimode fiber (MM) 50/125 µm	-
Multimode fiber (MM) 62.5/125 µm	-
Single mode fiber (SM) 9/125 µm	-
Single mode fiber (LH) 9/125 µm (long haul transceiver)	-
Power requirements	
Operating voltage	Power supply via the backplane of the MICE switch
Power consumption	0.8 W
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 70 °C
Protective paint on PCB	No
Relative humidity (non-condensing)	10 % ... 95 %
Mechanical construction	
Dimensions (W x H x D)	38 mm x 134 mm x 118 mm
Mounting	Backplane
Weight	n/a
Protection class	IP20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13,2 Hz, 90 min.; 0,7g, 13,2 Hz - 100 Hz, 90 min.; 3,5 mm, 3 Hz - 9 Hz, 10 Zyklen, 1 Oktave/min.; 1g, 9 Hz - 150 Hz, 10 Zyklen, 1 Oktave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Scope of delivery and accessories	
Scope of delivery	Module, operating manual
Accessories to order separately	ML-MS2/MM labels



HIRSCHMANN

A **BELDEN** BRAND

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.