



## Product information RPS60/48V EEC

Industrial Ethernet: System Accessories: Power supply: RPS60/48V EEC

<http://e-catalog.hirschmann.com/link/57078-24455-24544-24545-40457/en/conf/uisstate>

Name	RPS60/48V EEC
	
	48 V DC rail power supply unit
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	48 V DC rail power supply unit
Type	RPS60/48V EEC
Order No.	943 952-001
<b>More Interfaces</b>	
Voltage input	1 Federkraft-Klemmblock, 4-polig
Voltage output	1 Federkraft-Klemmblock, 4-polig
<b>Power requirements</b>	
Operating voltage	230 V
<b>Input data</b>	
230 V	100 to 240 V AC; 50-60Hz or 85 to 264 V AC; 47-63Hz (DC 100 to 375V)
<b>Current consumption</b>	
230 V	Max. 0.7 A at 230 V max. 1.3 A at 100V
Activation current	< 40 A at 264 V AC
<b>Output data</b>	
Output voltage	47-52 V DC (typ. 48 V); externally adjustable
<b>Output current</b>	
230 V	1,25 A static at 48 V nominal 1,88 A (150% of nominal load) for max. 2,5 seconds
<b>Service</b>	
Diagnostics	LED (green)
<b>Ambient conditions</b>	
Operating temperature	-20 °C to +70 °C
Storage/transport temperature	-25 °C to +85 °C
Relative humidity (non-condensing)	max. 95 % without condensation
<b>Mechanical construction</b>	
Dimensions (W x H x D)	44,8 mm x 75 mm x 104,5 mm
Mounting	DIN Rail 35 mm
Weight	245 g
Protection class	IP 20
<b>EMC interference immunity</b>	
EN 50082-1	EN 61000-6-1
EN 50082-2	EN 61000-6-2
<b>EMC emitted immunity</b>	
EN 50081-1	61000-6-3, 61000-6-4, EN 55011, EN 55022 class A
EN 50081-2	harmonic input current, fulfills EN 61000-3-2
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508 (pending)
Safety of information technology equipment	cUL 60950-1 (pending)
Hazardous locations	cUL 1604 Class1 Div 2

Industrial Ethernet: System Accessories: Power supply: RPS60/48V EEC

<http://e-catalog.hirschmann.com/link/57078-24455-24544-24545-40457/en/conf/ui/state>

**Scope of delivery and accessories**

<b>Scope of delivery</b>	Rail power supply, ferrit with safety key, Description and operating manual
--------------------------	--

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.