




Product information BAT300-F

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-F:BAT300-F

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24497-78529-46009/en/conf/uisstate>

Name	BAT300-F
	
	Dualband Ruggedized Industrial Wireless LAN Access Point/Client with one radio module with IEEE 802.11n for installation in harsh environment.
Delivery informations	
Availability	available
Product description	
Description	Dualband Ruggedized Industrial Wireless LAN Access Point/Client with one radio module with IEEE 802.11n for installation in harsh environment.
Port type and quantity	1 x WLAN interface, up to 8 SSIDs per WLAN interface, one LAN ports 10/100BASE-TX, autosensing, Power over Ethernet according to IEEE 802.3af
Type	BAT300-F
Order No.	943 959-118
Radio technology	
Antenna connector	3 x N jack antenna connectors
Range	depending on type of antenna, frequency range and data rate - please use the antenna distance calculator
Frequency band	1 x radio module, supporting 2.4 GHz and 5 GHz: 2400-2483.5 MHz (ISM) and 5170-5850 MHz
Modulation	22M0F7D(DSSS/OFDM) @ 2.4 GHz 20M0G7D (OFDM) @ 5 GHz
Radio topology	WLAN access point, bridge, router, point-to-point, client, client-bridge mode, WDS - Wireless Distribution System, fixed mesh with RSTP
Power requirements	
Operating voltage	2 x DC 24 V; 1 x Power-over-Ethernet according to IEEE802.3af; all power supplies redundant to each other
Current consumption at 24 V DC	417 mA
Current consumption	DC 12 V: 625 mA; DC 24 V: 417 mA; PoE (48 V DC): 167 mA
Ambient conditions	
Operation temperature	-30 °C to +55 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity (non-condensing)	max. 95%
MTBF	43.3 years
Mechanical construction	
Dimensions (W x H x D)	261 mm x 189 mm x 55 mm
Mounting	for wall and mast mounting
Protection class	IP 65, IP 67
Approvals	
Safety of information technology equipment	EN 60950
Radio	EN 300328, EN 301893, notified in all countries of EU. For other notifications or certifications please refer to INET-Sales@hirschmann.de
Environmental	EN 61000-6-2, EN 61131 for use in automation environment; E1 certification for use in vehicles; EN50155 for use in trains; Tested for salt spray according to DIN EN 60068-2-52
Scope of delivery and accessories	
Scope of delivery	Device, 3 dipole antennas, CD, M12 connector, 2 x 50 Ohm terminator, mounting material
Accessories to order separately	External antennas for 802.11b/g/n and 802.11a/h/n operation adapter cable and surge arrester, mast mount material

For more information please contact:

Hirschmann Automation and Control GmbH
Stuttgarter Strasse 45-51



HIRSCHMANN

A **BELDEN** BRAND

72654 Neckartenzlingen
Germany
Phone: +49 7127/14-1809
E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.