




Product information ACA11-miniDIN (EEC)

Industrial Ethernet: System Accessories: Adapter cable: ACA11-miniDIN (EEC)
<http://e-catalog.hirschmann.com/link/57078-24455-24544-40965/en/conf/uisstate>

Name	ACA11-miniDIN (EEC)
	

Auto-configuration adapter with extended temperature range saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and quickly replaced.

Delivery informations

Availability	available
--------------	-----------

Product description

Description	Auto-configuration adapter with extended temperature range saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and quickly replaced.
-------------	--

Type	ACA11-miniDIN (EEC)
------	---------------------

Order No.	943 973-001
-----------	-------------

More Interfaces

To the RS232 interface on the switch	RJ11 connector
--------------------------------------	----------------

To the RS232 interface on the PC or notebook	n/a
--	-----

To the USB interface on the switch	n/a
------------------------------------	-----

Power requirements

Operating voltage	via the RS232 interface on the switch
-------------------	---------------------------------------

Service

Diagnostics	writing to ACA, reading from ACA, writing/reading not OK; (display using LEDs on the switch)
-------------	---

Configuration	via the RS232 interface of the switch and via SNMP/Web
---------------	--

Ambient conditions

Operating temperature	-40 °C ... 70 °C
-----------------------	------------------

Storage/transport temperature	-40 °C ... 85 °C
-------------------------------	------------------

Relative humidity (non-condensing)	10 % ... 95 %
------------------------------------	---------------

MTBF	370.9 years (MIL-HDBK-217F)
------	-----------------------------

Mechanical construction

Dimensions (W x H x D)	90 mm x 27 mm x 12 mm
------------------------	-----------------------

Mounting	plug-in module
----------	----------------

Weight	35 g
--------	------

Protection class	IP40
------------------	------

Cable length	31.5 cm
--------------	---------

Mechanical stability

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
----------------------	---------------------------------

IEC 60068-2-6 vibration	1 g, 10 Hz - 150 Hz, 30 cycles
-------------------------	--------------------------------

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
--	--

EN 61000-4-3 electromagnetic field	10 V/m
------------------------------------	--------

EMC emitted immunity

EN 55022	EN 55022
----------	----------

Approvals

Hazardous locations	cUL 1604 Class1 Div 2 (pending)
---------------------	---------------------------------

Shipbuilding	Germanischer Lloyd (pending)
--------------	------------------------------

Safety of information technology equipment	cUL 60950-1 (pending)
--	-----------------------

Safety of industrial control equipment	cUL 508
--	---------

Employment in vehicles	E1
------------------------	----

Industrial Ethernet: System Accessories: Adapter cable: ACA11-miniDIN (EEC)

<http://e-catalog.hirschmann.com/link/57078-24455-24544-24546-40965/en/conf/ui/state>

Scope of delivery and accessories

Scope of delivery	device, operating manual
--------------------------	--------------------------

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.