




## Product information BAT-ANT-N-LC-G-50m-IP65

Industrial Ethernet:Industrial Wireless LAN:Accessories:Antenna:BAT-ANT-N-LC-G-50m-IP65

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24498-24499-40994/en/conf/ui/istate>

Name	BAT-ANT-N-LC-G-50m-IP65
	
	Leaky Cable for 2.4GHz; black
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Leaky Cable for 2.4GHz; black
Type	BAT-ANT-N-LC-G-50m-IP65
Order No.	943 981-001
Cable length	50 m
Cable specification	2 x N male connectors; 1.5 dB at 2.4GHz
<b>Radio technology</b>	
Range	-
Frequency band	2000 MHz - 2900 MHz
Polarisation	-
Elevation, Azimuth	-
VSWR	-
Gain	Longitudinal Attenuation between 2.4 and 2.485 GHz; LC at 10 cm from a concrete floor 15 dB/100 m; LC bei 15 mm from a metal surface 17 dB/100 m; LC directly against a metal surface 34 dB/100 m
Antenna connector	N-connector
<b>Ambient conditions</b>	
Operating temperature	-40 °C to +85 °C
Storage/transport temperature	-70 °C to +85 °C
Wind load	-
<b>Mechanical construction</b>	
Dimensions (W x H x D)	50m; d=15mm
Mounting	wall, minimum bending radius, single bend mm (in) 200 (7.87)
Protection class	IP 65
Material	-
Weight	12 kg
<b>Scope of delivery and accessories</b>	
Scope of delivery	Leaky Cable, 2 x N-connector preassembled, 1 x terminator 50 Ohm, 50 x fastening clip

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.