




Product information BAT-ANT-N-MiMo5-9N-IP65

Industrial Ethernet:Industrial Wireless LAN:Accessories:Antenna:BAT-ANT-N-MiMo5-9N-IP65

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24498-24499-65378/en/conf/uisstate>

Name	BAT-ANT-N-MiMo5-9N-IP65
	
	5 GHz MiMo antenna for sectoral illumination
Delivery informations	
Availability	available
Product description	
Description	5 GHz MiMo antenna for sectoral illumination
Type	BAT-ANT-N-MiMo5-9N-IP65
Order No.	943 981-013
Cable length	3 x 90 cm directly attached
Cable specification	N-plug
Radio technology	
Range	please refer to the antenna distance calculator
Frequency band	5150 MHz - 5875 MHz
Polarisation	triple linear, 45° slant
Elevation, Azimuth	3 dB beam width 60° / 60°
VSWR	1.5
Gain	9 dBi
Antenna connector	N male
Ambient conditions	
Operating temperature	-40 °C to +80 °C
Storage/transport temperature	-40 °C to +80 °C
Wind load	15 N at 160 km/h
Mechanical construction	
Dimensions (W x H x D)	101 mm x 80 mm x 35 mm
Mounting	wall, mast
Protection class	IP65
Material	LEXAN EXL 9330
Weight	0.11 kg
Scope of delivery and accessories	
Scope of delivery	antenna, mounting material, 3x pigtail N to RP-SMA

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.